

## ECLIPSE® LOW ODOR STRIPPER

*Extra strength floor stripper formulated for use in environments where odor is a problem*

### FEATURES

- No offensive odor
- Non-butyl - lower toxicity
- Non-caustic
- Labor savings - emulsifies floor coatings and sealers fast
- Easy application with mop or autoscrubber
- Super-concentrated for economical use



### RECOMMENDED FLOOR SURFACES

All resilient tile flooring, linoleum and most types of terrazzo, marble and quarry tile.

Not recommended for asphalt or rubber tile flooring.

**NOTE:** Test floor for color fastness in an inconspicuous area.

### PRODUCT DATA

|                         |   |
|-------------------------|---|
| Description:            | Non-butyl, low odor stripper                        |
| Appearance:             | Clear, red liquid                                   |
| Fragrance:              | None  |
| Viscosity (Brookfield): | < 5 centipoise @ 68°F (20°C)                        |
| Flash Point:            | >200°F (93°C), ASTM method D56                      |
| Shelf Life:             | 2 years, ASTM D1791-93 (1998)                       |
| Density:                | 8.7 lb per gal at 68°F<br>1.04 kg per liter at 20°C |
| Freeze/Thaw:            | Passes 3 cycles ASTM D3209-93 (1998)                |

### PRECAUTIONS

Keep out of reach of children. Keep container sealed when not in use. Keep from freezing. Combustible. Gloves and safety glasses recommended. Floor may become very slippery. Wear appropriate non-slip safety shoes. This product should not be used in contact with asphalt or rubber tile flooring, wood, or painted surfaces. Please read the Material Safety Data Sheet before handling this product.

### ORDERING INFORMATION

|                 |  |
|-----------------|--|
| Product #510FS: | 2 x 2.50 gallon per case (2 x 9.5 liter) |
| Product #510MP: | 4 x 1.06 gallon per case (4 x 4 liter)   |

### DIRECTIONS FOR USE

1. Mix Eclipse Low Odor Stripper in a mop bucket or autoscrubber per the following dilution ratios:

#### Light Stripping (FLOORMATTE™ Finish)

1:10 13 US oz per gallon warm water  
(0,5 liter per 5 liters warm water)

#### Medium Stripping (Most Finishes)

1:8 16 US oz per gallon warm water  
(0,62 liter per 5 liters warm water)

#### Heavy Stripping (Equinox®, Sealers, etc.)

1:6 21.5 US oz per gallon of warm water  
(0,83 liter per 5 liters of warm water)

2. Apply solution liberally to the floor and allow to soak for 10 minutes. Do not allow stripper solution to dry on floor.
3. Scrub floor with recommended Pioneer Eclipse autoscrubber or stripping machine with Pioneer Eclipse pad(s) or brushes.
4. Pick up dirty solution with autoscrubber or wet vac.
5. Use a clean mop or autoscrubber to rinse floor twice with a Pioneer Eclipse neutral cleaner following label directions.
6. Rinse floor again with clean cold water. Allow to dry thoroughly before applying sealer or coating.

**NOTE:** Works most effectively in warm water. Test floor for color fastness in an inconspicuous area.

*Pioneer Eclipse®*

**ECLIPSE LOW ODOR STRIPPER**

**LAST REVISION DATE:** 03/07/06  
**MANUFACTURER:** Pioneer Eclipse® Corporation  
 Sparta, NC 28675 Phone: 1-336-372-8080  
**FOR CHEMICAL EMERGENCY:** Spill, Leak, Fire,  
 Exposure or Accident **CALL CHEMTREC - Day or  
 Night 1-800-424-9300** Toll Free in the  
 Continental US **483-7616** in DISTRICT OF  
 COLUMBIA. For calls originating outside the US:  
 Call Collect **1-202-483-7616** Washington, DC.

**SECTION I: GENERAL INFORMATION**

**PRODUCT NAME:** Eclipse Low Odor Stripper  
**PRODUCT #:** 510  
**PRODUCT TYPE:** Non-butyl, low odor stripper  
**PRECAUTIONS:** Severe irritant. Do not get in eyes,  
 on skin or clothing. Avoid breathing vapor. Keep  
 container sealed when not in use. Keep out of  
 reach of children.  
**HEALTH:** 2  
**FLAMMABILITY:** 1  
**REACTIVITY:** 0  
**NFPA HAZARD RATINGS**



4-EXTREME 3-HIGH 2-MODERATE  
 1-SLIGHT 0-INSIGNIFICANT

**SECTION II: HAZARDOUS INGREDIENTS**

**INGREDIENT:** Monoethanolamine  
**CAS#:** 141-43-5  
**%:** 10-15  
**OSHA PEL:** 3 ppm (TWA)  
**ACGIH TLV:** 6 ppm (STEL) 3 ppm (TWA)  
**LD<sub>50</sub> SPECIES & ROUTE:** 1.2 g/kg rat, oral  
**INGREDIENT:** Benzyl Alcohol  
**CAS#:** 100-51-6  
**%:** 15-20  
**OSHA PEL:** N/E  
**ACGIH TLV:** N/E  
**LD<sub>50</sub> SPECIES & ROUTE:** 1.23 g/kg rat, oral

N/E = Not Established, N/L = Not Listed,  
 N/A = Not Applicable

**SECTION III: PHYSICAL/CHEMICAL DATA**

**APPEARANCE:** Clear, red liquid  
**PHYSICAL STATE:** Liquid  
**pH:** 12.4 ± 0.5  
**BOILING POINT:** 104°C / 220°F  
**EVAPORATION RATE:** Less than water  
**FREEZING POINT:** N/E  
**VAPOR DENSITY:** Less than air  
**VOLATILE BY WEIGHT:** 85-95%  
**VAPOR PRESSURE:** Less than water  
**DENSITY:** 8.7 lb per gal @ 68°F  
 1.04 kg per liter @ 20°C  
**SOLUBILITY IN WATER:** Miscible

**SECTION IV: FIRE AND EXPLOSION DATA**

**FLASH POINT:** >200°F (93°C) ASTM method D56  
**EXPLOSIVE LIMITS:**  
 LOWER: N/E UPPER: N/E  
**EXTINGUISHING MEDIA:** Water spray, CO<sub>2</sub>, dry  
 chemical, alcohol-type or universal type foams.

**SPECIAL FIRE FIGHTING PROCEDURES:**

Do not spray a solid stream of water or foam  
 directly into hot liquid. This may cause frothing.  
 Firefighters should wear NIOSH approved  
 breathing apparatus.

**HAZARDOUS COMBUSTIBLE PRODUCTS:** N/A  
**UNUSUAL FIRE AND EXPLOSION HAZARDS:**  
 Materials can splatter above 100°C / 212°F.

**SECTION V: REACTIVITY DATA**

**STABILITY:** Stable

**HAZARDOUS POLYMERIZATION:** Will not occur.

**INCOMPATIBILITY (MATERIALS TO AVOID):**

Strong acids and strong oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Carbon monoxide, carbon dioxide and  
 nitrogen oxides.

**REACTIVITY CONDITIONS:** None

**SECTION VI: HEALTH HAZARD DATA**

**EYES:** May cause severe burns or possible  
 corneal damage. For eye contact, flush with a  
 large amount of water for at least 15 minutes.  
 See a physician immediately.

**SKIN:** Irritation, reddening or possible damage  
 upon repeated or prolonged contact. For skin  
 contact, wash affected areas with soap and  
 water. Seek medical attention if irritation persists.

**INHALATION:** Vapor or mist can cause headache,  
 nausea and irritation of the eyes, nose, throat and  
 lungs. For overexposure, move subject to fresh  
 air. Seek medical attention if symptoms persist.

**INGESTION:** May cause nausea, abdominal  
 discomfort, vomiting, diarrhea. If ingested, give  
 two glasses of water or milk and do not induce  
 vomiting. Remove by endotracheal intervention.  
 Seek medical attention immediately.

**CHRONIC EFFECTS AND MEDICAL CONDITIONS**

**AGGRAVATED BY OVEREXPOSURE:** Main  
 hazard is due to product's severe irritant  
 properties. Treatment should be directed at  
 the control of symptoms and the clinical  
 condition of the patient.

**CARCINOGEN:** Non-carcinogenic

**REPRODUCTIVE EFFECTS:** N/E

**TERATOGENICITY:** N/E

**MUTAGENICITY:** N/E

**THRESHOLD LIMIT VALUE:** See Section II.

**SECTION VII: SPILL, LEAK & DISPOSAL PROCEDURES**

**SMALL SPILLS:** Absorb spill with inert material  
 (e.g. sand, earth) and dispose of as waste  
 material in accordance with local, state and  
 federal regulations.

**LARGE SPILLS:** Keep spectators away. Floors  
 may be slippery; use care to avoid falling. Dike  
 and contain spill with inert material (e.g. sand,  
 earth). Transfer liquid to containers for recovery or  
 disposal and solid diking material to separate  
 containers for disposal. Keep spills and cleaning  
 runoff out of sewers and open bodies of water.

**WASTE DISPOSAL:** Landfill or incinerate the  
 contaminated solids and diking material  
 according to local, state and federal regulations  
 concerning disposal of hazardous materials.  
 Non-salvageable liquid should be drummed and  
 turned over to a licensed hazardous waste  
 disposal facility.

**SECTION VIII: SPECIAL PROTECTION**

**EYE PROTECTION:** Chemical splash goggles  
 (ANSI Z87.1-1989 or approved equivalent)

**RESPIRATORY PROTECTION:** None required  
 when permissible airborne concentrations are  
 not exceeded. In emergency, use approved  
 positive pressure self-contained breathing device.

**VENTILATION:** Mechanical local exhaust  
 ventilation at point of contamination release

**OTHER PROTECTIVE EQUIPMENT:** As required  
 by employer code. Rubber boots and chemical  
 resistant gloves recommended.

**SECTION IX: SPECIAL PRECAUTIONS**

**HANDLING AND STORAGE:**

Storage temperature (MAX. 60°C / 140°F)  
 (MIN. 1°C / 34°F).

**OTHER PRECAUTIONS:** Keep from freezing.

**SECTION X: ADDITIONAL INFORMATION**

Neither this data sheet nor any statement  
 contained herein grants or extends any license,  
 expressed or implied, in connection with patents  
 issued or pending which may be the property of  
 the manufacturer or others. The information in  
 this data sheet has been assembled by the  
 manufacturer based on its own studies and the  
 work of others. The manufacturer makes no  
 warranties, expressed or implied, as to the  
 accuracy, completeness or adequacy of the  
 information contained herein. The manufacturer  
 shall not be liable (regardless of fault) or the  
 vendee, the vendee's employees or anyone for  
 any direct, special or consequential damages  
 arising out of or in connection with the  
 accuracy, completeness, adequacy or  
 furnishing of such information.

This MSDS has been provided to you in  
 accordance with the OSHA HAZARD  
 COMMUNICATION STANDARD (29CFR1910.1200).

\*\*\*IMPORTANT SAFETY INFORMATION  
 DO NOT DISCARD\*\*\*

\*\*PLEASE ROUTE TO COMPANY SAFETY OFFICER\*\*

Pioneer Eclipse®