

MATERIAL SAFETY DATA SHEET

Page 1 of 4

MSDS # 126847001

GLADE PLUG-INS SCENTED OIL - SKY BREEZE

Date Issued: 13Apr2004

Supersedes: 01Aug2000

US MANUFACTURER:

S.C. Johnson & Son, Inc.
Phone: (800) 725-6737
Racine, Wisconsin 53403-2236
Emergency Phone: (866) 231-5406
International Emergency Phone:
(952) 852-4647

CANADIAN MANUFACTURER:

S.C. Johnson and Son, Limited
Phone: (800) 725-6737
1 Webster Street
Brantford, Ontario N3T 5R1
Transportation Emergency:
CANUTEC (collect) (613) 996-6666
Poison Control: (866) 231-5406

HAZARD RATING	HMIS	HAZARD	NFPA	DISTRIBUTED IN CANADA BY:
-----	-----	-----	-----	S.C. Johnson and Son, Limited
4-Very High	2	Health	2	Phone: (800) 725-6737
3-High	2	Flammability	2	1 Webster Street
2-Moderate	0	Reactivity	0	Brantford, Ontario N3T 5R1
1-Slight		Special		
0-Insignificant				

SECTION 1 - PRODUCT IDENTIFICATION

PRODUCT NAME..... GLADE PLUG-INS SCENTED OIL - SKY BREEZE
REASON FOR CHANGE..... No significant changes.
PRODUCT USE..... Household: Air care

SECTION 2 - INGREDIENT INFORMATION

INGREDIENT	WEIGHT%	EXPOSURE LIMIT/TOXICITY
-----	-----	-----
Mixture of perfume oils.....	60-100	NOT ESTABLISHED

SECTION 3 - HEALTH HAZARDS IDENTIFICATION (Also See Section 11)

ROUTE(S) OF ENTRY..... Skin contact. Eye contact.
EFFECTS OF ACUTE EXPOSURE:
EYE..... May cause: Moderate eye irritation.
SKIN..... Prolonged or repeated contact may cause: Drying/defatting of skin.
INHALATION..... Irritation to nose, throat and respiratory tract.
INGESTION..... May cause irritation to mouth, throat and stomach.
MEDICAL CONDITIONS..... Persons with pre-existing skin disorders may be more susceptible
GENERALLY RECOGNIZED AS BEING AGGRAVATED BY EXPOSURE to irritating effects.

SECTION 4 - FIRST AID MEASURES

EYE CONTACT..... Flush immediately with plenty of water for at least 15 to 20 minutes. If irritation persists, get medical attention.
SKIN CONTACT..... Wash contaminated area with water and soap. If irritation persists, get medical attention.
INHALATION..... Remove to fresh air.
INGESTION..... Rinse mouth immediately. Immediately drink 1-2 glasses of water
Seek immediate medical attention.

SECTION 5 - FIRE AND EXPLOSION INFORMATION

FLASH POINT..... 151°F (66°C) (TCC)

MATERIAL SAFETY DATA SHEET

Page 2 of 4

MSDS # 126847001

GLADE PLUG-INS SCENTED OIL - SKY BREEZE

Date Issued: 13Apr2004

Supersedes: 01Aug2000

----- SECTION 5 - FIRE AND EXPLOSION INFORMATION (continued) -----

FLAMMABLE LIMITS.....	Not available.
AUTOIGNITION.....	Not available.
TEMPERATURE	
EXTINGUISHING MEDIA....	Foam. CO2. Dry chemical.
SPECIAL FIREFIGHTING... PROCEDURES	Fire fighters should wear self-contained breathing apparatus and protective clothing.
UNUSUAL FIRE AND..... EXPLOSION HAZARDS	No special hazards known.

----- SECTION 6 - PREVENTIVE RELEASE MEASURES -----

STEPS TO BE TAKEN IN... CASE MATERIAL IS RELEASED OR SPILLED	Eliminate all ignition sources. Dike large spills. Do not let spilled or leaking material enter watercourse. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize.
--	--

----- SECTION 7 - HANDLING AND STORAGE -----

PRECAUTIONARY..... INFORMATION	WARNING: Skin and eye irritant. Do not get in eyes, on skin or on clothing. If such contact occurs, flush immediately with plenty of water for at least 15 to 20 minutes. If irritation persists, seek medical aid. Keep out of reach of children.
OTHER HANDLING AND..... STORAGE CONDITIONS	Store in a cool, dry place with adequate ventilation. Observe good personal hygiene practices.

----- SECTION 8 - SPECIAL PROTECTION INFORMATION -----

RESPIRATORY PROTECTION. VENTILATION.....	No special requirements under normal use conditions. General room ventilation is normally adequate. Substantial amounts of mists/vapors can be controlled with local exhaust ventilation or respiratory protection.
PROTECTIVE GLOVES.....	If prolonged or repeated contact is possible: Any impervious material.
EYE PROTECTION.....	Chemical splash-proof goggles.
OTHER PROTECTIVE..... MEASURES	If major exposure is possible to eyes/skin, wear/use appropriate protective equipment.

----- SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES -----

COLOR.....	Clear Yellow
PRODUCT STATE.....	Liquid.
ODOR.....	Fragrant
pH.....	Not available.
ODOR THRESHOLD.....	Not available.
SOLUBILITY IN WATER....	Negligible
SPECIFIC GRAVITY..... (H2O=1)	0.91
VISCOSITY.....	Not available
VAPOR DENSITY (AIR=1)..	> 1
EVAPORATION RATE (BUTYL ACETATE=1)	Not available.
VAPOR PRESSURE (mm HG).	~ 1.00
BOILING POINT.....	Not available.
FREEZING POINT.....	Not available.

MATERIAL SAFETY DATA SHEET

Page 3 of 4

MSDS # 126847001

GLADE PLUG-INS SCENTED OIL - SKY BREEZE

Date Issued: 13Apr2004

Supersedes: 01Aug2000

----- SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES (continued) -----

COEFFICIENT OF..... Not available.
WATER/OIL
PERCENT VOLATILE BY.... > 99
VOLUME (%)
VOLATILE ORGANIC..... Not applicable.
COMPOUND (VOC)
THEORETICAL VOC..... Not applicable.
(LB/GAL)

----- SECTION 10 - STABILITY AND REACTIVITY -----

STABILITY..... Stable
STABILITY - CONDITIONS. Not available.
TO AVOID
INCOMPATIBILITY..... Strong acids (eg., muriatic acid). Strong oxidizing materials
(e.g. liquid chlorine).
HAZARDOUS DECOMPOSITION PRODUCTS When exposed to fire: Produces normal products of combustion.
HAZARDOUS..... Will not occur.
POLYMERIZATION
HAZARDOUS..... Not applicable.
POLYMERIZATION -
CONDITIONS TO AVOID

----- SECTION 11 - TOXICOLOGY INFORMATION (Also See Section 3) -----

LD50 (ACUTE ORAL TOX).. Not available.
LD50 (ACUTE DERMAL TOX) Not available.
LC50 (ACUTE INHALATION. Not available.
TOX)
EFFECTS OF CHRONIC..... None known.
EXPOSURE
SENSITIZATION..... None known.
CARCINOGENICITY..... None known.
REPRODUCTIVE TOXICITY.. None known.
TERATOGENICITY..... None known.
MUTAGENICITY..... None known.

----- SECTION 12 - ECOLOGICAL INFORMATION -----

ENVIRONMENTAL DATA..... Not available.

----- SECTION 13 - DISPOSAL CONSIDERATIONS -----

WASTE DISPOSAL..... Observe all Federal, Provincial, State and Municipal
INFORMATION regulations.

----- SECTION 14 - TRANSPORTATION INFORMATION -----

US DOT INFORMATION..... Please refer to the Bill of Lading/receiving documents for
up-to-date shipping information.

MATERIAL SAFETY DATA SHEET

Page 4 of 4

MSDS # 126847001

GLADE PLUG-INS SCENTED OIL - SKY BREEZE

Date Issued: 13Apr2004

Supersedes: 01Aug2000

----- SECTION 14 - TRANSPORTATION INFORMATION (continued) -----

CANADIAN SHIPPING NAME. GLADE PLUG-INS SCENTED OIL - SKY BREEZE
TDG CLASSIFICATION..... Not applicable.
PIN/NIP..... Not applicable.
PACKING GROUP..... Not applicable.
EXEMPTION NAME..... Not applicable.

----- SECTION 15 - REGULATORY INFORMATION -----

WHMIS CLASSIFICATION... Non-regulated.

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

All ingredients in this product comply with the New Substances Notification requirements under the Canadian Environmental Protection Act (CEPA).

This product is not subject to the reporting requirements under California's Proposition 65.

----- SECTION 16 - OTHER INFORMATION -----

ADDITIONAL INFORMATION. Use as directed.
EPA REGISTRATION #..... Not applicable.

----- PREPARATION INFORMATION -----

PREPARED BY..... Manufacturer's Technical Support Department. Refer to page 1
(Manufacturer) for contact information.

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained herein. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

PRINT DATE: 12Oct2005