

## Material Safety Data Sheet This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200



WHMIS Class E: Corrosive liquid. WHMIS Class D-2B: Material causing other toxic effects (TOXIC).

HCS CLASS: Corrosive liquid.

WHMIS (Pictograms)

WHMIS (Classification)

HCS

Section 1. Che	emical Product and Company Identification		
Product Name/ Trade name	Ax It	Code	151
Synonym	Very Aggressive No-Rinse Stripper	CAS#	Not applicable.
Chemical Family	Not available.	Validation I	Date 5/31/2005
Chemical Formula	Not applicable.	Print Date	5/31/2005
Manufacturer/ Supplier	•	In Case of Emergency	Chemtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS	<b>E</b>	Protective Clothing

Section 2. Composition and Information on Ingredients				
Name	CAS#	% by Weight	Exposure Limits	LC <sub>50</sub> /LD <sub>50</sub>
2-Butoxyethanol	111-76-2	10 - 15	ACGIH (United States). TWA: 20 ppm OSHA (United States). TWA: 50 ppm	ORAL (LD50): Acute: 1746 mg/kg [Rat].
Potassium Hydroxide	1310-58-3	5 - 10	Not available.	Not available.
Sodium Xylene Sulfonate	1300-72-7	<7	Not available.	ORAL (LD50): Acute: 650 mg/kg [Rat]. 5939 mg/kg [Mouse].
Monoethanolamine	141-43-5	1 - 5	TWA: 3 ppm OSHA (United States). TWA: 6 ppm STEL: 6 ppm	Not available.

Section 3. Hazards Identification		
Potential Acute Health Effects	Corrosive to skin and eyes on contact. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath.	
Potential Chronic Health Effects	May aggravate existing respiratory conditions such as asthma. Severe over exposure may cause nervous system damage and kidney damage. Repeated or prolonged exposure to the substance may produce liver damage, blood disorders.	
Carcinogenic Effects	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.	

Section 4. Fire	st Aid Measures
Eye Contact	Avoid contact with eyes Call a poison control center or doctor immediately for treatment advice. Hold eye open and rinse slowly and thoroughly with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
Skin Contact	Rinse skin immediately with plenty of water for 15 to 20 minutes.
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible.
Ingestion	Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person

Section 5. Fire Fighting Measures	
<b>Products of Combustion</b>	Not available.
Fire Fighting Media and Instructions	Non-flammable substance.
Special Remarks on Fire Hazards	No additional remark.
Special Remarks on Explosion Hazards	No additional remark.

Section 6. Accidental Release Measures		
Small Spill and Leak	Absorb with an inert material and place in an appropriate waste disposal container.	
Large Spill and Leak	Corrosive liquid. Do not touch damaged container or spilled material. Isolate the area, do not attempt to clean-up spill, notify your manager for additional instructions.	
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.	

Section 7. Handling and Storage		
Precautions	After handling, always wash hands thoroughly with soap and water. Do not breathe gas/fumes/ vapor/spray. Do not ingest. Good general ventilation should be sufficient to control airborne levels.	
Incompatibility	acids , oxidizing materials, metals	
Storage	Corrosive materials should be stored in a separate safety storage cabinet or room. Handle and open container with care Keep out of the reach of children. Not for use or storage in or around the home.	

Section 8. Exposure Controls/Personal Protection		
<b>Engineering Controls</b>	Good general ventilation should be sufficient to control airborne levels.	
Personal Protection  Eyes	Splash goggles.	
Body	Wear overalls or long sleeved shirt and long trousers, nitrile rubber or neoprene gloves, rubber boots.	
Respiratory	Wear appropriate respirator when ventilation is inadequate. Be sure to use a MSHA/NIOSH approved respirator or equivalent.	
Hands	Gloves (impervious).	

## Protective Clothing (Pictograms)









**Exposure Limits** 

**2-Butoxyethanol** TWA: 25 (ppm)

TWA: 50 (ppm) from OSHA (PEL)

Monoethanolamine

TWA: 3 (ppm)

TWA: 6 (ppm) from OSHA (PEL) STEL: 6 (ppm)

Consult local authorities for acceptable exposure limits.

uid. (Liquid.)  t applicable.  to 14 [Basic.]  4°F initial  t available.  t available.  t available.	Odor Taste Color	Characteristic.  Not available.  Colorless.
to 14 [Basic.]  4°F initial  t available.  t available.		
4°F initial t available. t available.	Color	Colorless.
t available. t available.		
t available.		
t available.		
4 (Water = 1)		
mm Hg @ 68°F		
(Air = 1)		
t available.		
compared to Water		
e solubility in water.		
sily soluble in cold water.		
y be combustible at high temperature.		
t available.		
t available.		
n flammable		
t	sily soluble in cold water.  y be combustible at high temperature. t available.	sily soluble in cold water.  y be combustible at high temperature.  t available.  t available.

Explosion Hazards in Presence of Various Substances Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: Not available.

Section 10. Stability and Reactivity Data	
Stability	The product is stable.
Incompatibility with Various Substances	acids , oxidizing materials, metals
Hazardous Decomposition Products	Will not occur.

Section 11. Toxicological Information		
<b>Routes of Entry</b>	Absorbed through skin. Eye contact. Inhalation. Ingestion.	
<b>Toxicity to Animals</b>	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE.  Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol).  Acute toxicity of the gas (LC50): 926 ppm 4 hour(s) [Mouse]. (2-Butoxyethanol).	
<b>Acute Effects on Humans</b>		
Eyes	Corrosive to eyes on contact. Eye contact can result in corneal damage or blindness.	
Skin	Corrosive to skin and eyes on contact. Tissue Destruction Possible. Skin contact may produce burns.	
Inhalation	The product is a severe irritant for lungs and respiratory tract. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract.	
Ingestion	Harmful if swallowed. Burns to mouth, throat and stomach. May be fatal if swallowed.	
Chronic Effects on Humans	May aggravate existing respiratory conditions such as asthma. Severe over exposure may cause nervous system damage and kidney damage. Repeated or prolonged exposure to the substance may produce liver damage, blood disorders.	
Special Remarks on Toxicity to Animals	No additional remark.	
Special Remarks on Chronic Effects on Humans	No additional remark.	

Section 12. Ecological Information		
Ecotoxicity	Not available.	
BOD5 and COD	Not available.	
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.	
Toxicity of the Products of Biodegradation	of Not available.	
Special Remarks on the Products of Biodegradation	No additional remark.	

## Section 13. Disposal Considerations

Waste Information Any method in accordance with applicable laws.

Waste Stream Not available.

## Section 14. Transport Information

DOT (U.S.A) (Pictograms)



**TDG Classification** 

8



Specific Hazard

PIN UN, Proper Shipping Shipping name: Corrosive liquids n.o.s. UNNA: UN1760 PG: II

The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product.

Name, PG

Maritime Transportation Not available.

**Special Provisions for** 

**Transport** 

Not available.

WHMIS (Classification)	WHMIS Class E: Corrosive liquid. WHMIS Class D-2B: Material causing other toxic effects (TOXIC).				
Regulatory Lists	No products were found.				
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).				
Other Classifications	HCS (U.S.A.)	HCS CLASS: Corrosive liquid.			
	USA Regulatory Lists				
		SARA 311/312 MSDS distribution - didentification: 2-Butoxyethanol: imme hazard; Potassium Hydroxide: imme SARA 313 toxic chemical notification 2-Butoxyethanol	ediate health hazard, delayed health ediate health hazard		
	DSD (EEC)	R35- Causes severe burns.			
	DSD (EEC)	NOO- Causes severe buills.			
	International Regulations Lists	No products were found.			

Section 16. Oth	er Information		
Validated by CRushton on 5/31/2005.		Verified by CRushton. Printed 5/31/2005.	
Information Contact	Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607		
Notice to Reader			

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 5/31/2005.	Ax It	Page: 6/6

Continued on Next Page