

# **Material Safety Data Sheet**

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200

CLASS E: Corrosive liquid.

Class: Corrosive material

WHMIS (Pictograms)

WHMIS (Classification)

**HCS** 

Section 1. Chemical Product and	I Company Identification
---------------------------------	--------------------------

Product Name/ Trade name	Betco Low Foam Chlorinated Degreaser	Code		530
Synonym	Chlorinated Degreaser	CAS#		Mixture
Chemical Family	Not available.	Validation D	ate	3/26/2004
Chemical Formula	Not applicable.	Print Date		3/27/2004
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Oh 43607 (419) 241-2156	In Case of Emergency	Chei	mtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.			
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS	1	Pro	tective Clothing

Section 2. Composition and Information on Ingredients				
Name	CAS#	% by Weight	Exposure Limits	$ m LC_{50}/LD_{50}$
1) Potassium Hydroxide	1310-58-3	5-10	Not available.	Not available.
2) Sodium Hypochlorite	7681-52-9	0-5	Not available.	Not available.
3) Sodium Silicate	1344-09-8	0-5	Not available.	Not available.
4) Sodium Tripolyphosphate	7758-29-4	0-1	Not available.	Not available.
5) Sodium 2-ethylhexyl sulfate	126-92-1	1-5	Not available.	ORAL (LD50): Acute: 3.7 mg/kg [Rat].
6) Surfactant	119345-04-9	0-5	Not available.	Not available.
7) Soda Ash	497-19-8	0-5	Not available.	Not available.
8) Potassium Silicate	10006-28-7	0-5	Not available.	Not available.

#### Section 3. Hazards Identification

Potential Acute Health Effects Corrosive to eyes and skin. Eye contact can result in corneal damage or blindness. Skin contact may produce burns. Workers whith the following conditions warrant particular attention: Persons with

existing respiratory ailments such as asthma or similar should avoid contact with this product. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by

coughing, choking, or shortness of breath.

**Potential Chronic Health** 

Effects

Over-exposure by inhalation may cause respiratory irritation. Prolonged exposure may result in skin burns and ulcerations. Repeated or prolonged contact with spray mist may produce chronic eye

irritation and severe skin irritation.

Carcinogenic Effects Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First	Aid Measures
Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Check for and remove any contact lenses, after the first 5 minutes, then continue rinsing the eye. Seek immediate medical attention.
Skin Contact	Flush with plenty of water for at least 15 minutes. Seek medical attention.
Inhalation	Evacuate the victim to a safe area as soon as possible. If the victim is not breathing, perform mouth-to-mouth resuscitation. SEEK IMMEDIATE MEDICAL ATTENTION
Ingestion	Do not induce vomiting. Have conscious person drink several glasses of water or milk. NEVER give an unconscious person anything to ingest. SEEK IMMEDIATE MEDICAL ATTENTION

Section 5. Fire Fighting Measures		
<b>Products of Combustion</b>	Chlorine	
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.	
Special Remarks on Fire Hazards	Not available.	
Special Remarks on Explosion Hazards	Not available.	

Section 6. Accidental Release Measures		
Small Spill and Leak	Dilute with water and mop up, or absorb with an inert dry material and place in an appropriate waste disposal container.	
Large Spill and Leak	Corrosive liquid. Poisonous liquid.  Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Use water spray to reduce vapors. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources.	
Personal Protection in Case o a Large Spill	f Splash goggles. Full suit. Boots. Gloves.	

Section 7. Hand	lling and Storage
Precautions	Keep locked up Keep container dry. Keep away from heat. Keep away from sources of ignition. Do not ingest. Do not breathe gas/fumes/ vapor/spray. Never add water to this product. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes Keep away from incompatibles such as oxidizing agents, acids.
Incompatibility	Extremely reactive or incompatible with oxidizing agents, acids. Extremely incompatible with ammonia. Incompatible with copper alloys. Incompatible with iron.
Storage	Corrosive materials should be stored in a separate safety storage cabinet or room. Keep container in a cool, well-ventilated area. Keep away from incompatibles. Must be stored in a dry location. Not for use or storage in or around the home. Keep out of the reach of children. Keep out of the reach of children.

Section 8. Exposure Controls/Personal Protection		
<b>Engineering Controls</b>	If user operations generate dust, fume or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit. Local exhaust ventilation should be provided.	
Personal Protection		
Eyes	s Splash goggles or Face shield.	
Body	Long Sleeves and Pants or overalls to avoid skin contact.	
Respiratory	Be sure to use a MSHA/NIOSH approved respirator or equivalent. Respirator with chlorine cartridge.	
Hands	Gloves, Butyl rubber.	

Protective Clothing (Pictograms)



Exposure Limits Not available.

Section 9. Physical a	and Chemical Properties		
Physical State and Appearance	Liquid.	Odor	Characteristic.
Molecular Weight	Not applicable.	Taste	
pН	13 to 14 [Basic.]	Color	Yellowish. (Light.)
<b>Boiling/Condensation Point</b>	>100°C (212°F)		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.16 (Water = 1)		
Vapor Pressure	2.4 kPa (@ 20°C)		
Vapor Density	>1 (Air = 1)		
Volatility	Not available.		
VOC	Not available.		
<b>Evaporation Rate</b>	<1 compared to Butyl acetate.		
Dispersion Properties	See solubility in water.		
Solubility	Easily soluble in cold water, hot water.		
The Product is:	May be combustible at high temperature.		
Auto-ignition Temperature	Not available.		
Flash Points	CLOSED CUP: >98.889°C (210°F).		
Flammable Limits	Not available.		
Fire Hazards in Presence of Various Substances	Not available.		
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of Risks of explosion of the product in presence of	of mechani of static dis	cal impact: Not available. charge: Not available.

Section 10. Stability and Reactivity Data		
Stability	The product is stable.	
Incompatibility with Various Substances	Extremely reactive or incompatible with oxidizing agents, acids. Extremely incompatible with ammonia. Incompatible with copper alloys. Incompatible with iron.	
Hazardous Decomposition Products	Chlorine; Hypochlorus Acid	

Section 11. Toxicolog	gical Information
Routes of Entry	Absorbed through skin. Eye contact. Inhalation. Ingestion.
<b>Toxicity to Animals</b>	Acute oral toxicity (LD50): 3.7 mg/kg [Rat]. (Sodium 2-ethylhexyl sulfate ).
Acute Effects on Humans	
Eyes	Extremely hazardous in case of eye contact (irritant, corrosive). Inflammation of the eye is characterized by redness, watering, and itching. Eye contact can result in corneal damage or blindness.
Skin	Very hazardous in case of skin contact (corrosive, irritant). Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.
Inhalation	Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Over-exposure by inhalation may cause respiratory irritation.
Ingestion	Very hazardous in case of ingestion. May be fatal if swallowed. May cause burns to mouth, throat, and stomach.
Chronic Effects on Humans	Over-exposure by inhalation may cause respiratory irritation. Prolonged exposure may result in skin burns and ulcerations. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.

Section 12. Ecological Information		
Ecotoxicity	Not available.	
BOD5 and COD	Not available.	
<b>Products of Biodegradation</b>	Not available.	
Toxicity of the Products of Biodegradation	Not available.	
Special Remarks on the Products of Biodegradation	Not available.	

Section 13. Disposal Considerations			
Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.		
Waste Stream	Not available.		

## Section 14. Transport Information

DOT (U.S.A) (Pictograms)



TDG Classification Class 8: Corrosive material



PIN UN, Proper Shipping Name, PG Shipping name: CORROSIVE LIQUIDS, N.O.S. (Sodium Hypochlorite, Potassium Hydroxide) UNNA: 1760 PG: II

Maritime Transportation Not available.

Special Provisions for

Not available.

Transport

WHMIS (Classification)	CLASS E: Corrosive liq	uid.		
Regulatory Lists	No products were found.			
Other Regulations	OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).			
Other Classifications	HCS (U.S.A.)	Class: Corrosive material		
	USA Regulatory Lists			
		SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Potassium Hydroxide: immediate health hazard		
	DSD (EEC)			
	DSD (EEC) International Regulations Lists			

Section 16. Othe	r Information		
Validated by CRushton on 3/26/2004.		Verified by CRushton. Printed 3/27/2004.	
Information Contact	Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607		

### Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 3/26/2004.

Betco Low Foam Chlorinated Degreaser

Page: 5/5

## Continued on Next Page