

# **Material Safety Data Sheet**

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200



WHMIS Class E: Corrosive liquid. WHMIS CLASS D-2: Material causing other toxic effects.

HCS Class: Corrosive liquid.

WHMIS (Pictograms)

WHMIS (Classification)

**HCS** 

Section 1. Che	Section 1. Chemical Product and Company Identification		
Product Name/ Trade name	Extreme	Code	184
Synonym	High Power/High Speed No Rinse Floor Stripper	CAS#	Not applicable.
Chemical Family	Not available.	Validation 1	Date 1/18/2005
Chemical Formula	Not applicable.	Print Date	1/18/2005
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607 (419) 241-2156	In Case of Emergency Chemtrec (800) 424-9300	
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS		Protective Clothing

Section 2. Composition and Information on Ingredients				
Name	CAS#	% by Weight	Exposure Limits	LC <sub>50</sub> /LD <sub>50</sub>
2-Butoxyethanol	111-76-2	<21	TWA: 20 (ppm) from ACGIH (TLV) [United States] TWA: 50 (ppm) from OSHA (PEL) [United States]	ORAL (LD50): Acute: 1746 mg/kg [Rat].
Benzyl Alcohol Monoethanolamine	100-51-6 141-43-5	<10 5-10	TWA: 3 STEL: 6 (ppm) TWA: 3 (ppm) TWA: 6 (ppm) from OSHA (PEL) [United States] STEL: 6 (ppm)	Not available. Not available.
Sodium Xylene Sulfonate  Mixed Amphocarboxylates	1300-72-7 N/A	<5 0-5	Not available.	ORAL (LD50): Acute: 650 mg/kg [Rat]. 5939 mg/kg [Mouse]. Not available.

### Section 3. Hazards Identification

Potential Acute Health Effects

Corrosive to eyes and skin. Harmful if swallowed. Harmful if inhaled. Irritating to mouth, throat and stomach.

Potential Chronic Health Effects

Asthma and related respiratory illness may be aggravated by exposure. Repeated or prolonged exposure to the gas can produce lung damage. Repeated or prolonged exposure to the substance can produce kidney damage. Repeated or prolonged exposure to the substance can produce liver damage. Repeated or prolonged exposure to the substance can produce nervous system damage. However, in light of good industrial hygiene, exposure to any chemical should be kept to a minimum.

Section 4. Fir	Section 4. First Aid Measures		
Eye Contact	Immediately Hold eye open and rinse slowly and thoroughly with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor immediately for treatment advice.		
Skin Contact	Remove contaminated clothing and shoes. Rinse skin with plenty of water for 15 to 20 minutes. Call a poison control center or doctor for further treatment advice.		
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible. Call a poison control center or doctor for further treatment advice.		
Ingestion	Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person		


Section 5. Fire Fighting Measures		
<b>Products of Combustion</b>	Not available.	
Fire Fighting Media and Instructions	N/A	
Special Remarks on Fire Hazards	N/A	
Special Remarks on Explosion Hazards	N/A	

Section 6. Accidental Release Measures		
Small Spill and Leak	Absorb with an inert material and place in an appropriate waste disposal container.	
Large Spill and Leak	Prevent entry into sewers, basements or confined areas. Neutralize caustic ingredients with vinegar or acetic acid or use a basic spill kit.	
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.	

Section 7. Han	ndling and Storage
Precautions	After handling, always wash hands thoroughly with soap and water. Avoid breathing vapors or spray mists. Do not ingest. Good general ventilation should be sufficient to control airborne levels.
Incompatibility	Strong acids or oxidizers.
Storage	Keep out of the reach of children. Not for use or storage in or around the home.

Section 8. Exposure Controls/Personal Protection		
<b>Engineering Controls</b>	Good general ventilation should be sufficient to control airborne levels.	
Personal Protection  Eyes	Splash goggles.	
Wear overalls or long sleeved shirt and long trousers, nitrile rubber or neoprene gloves, r boots.		
Respiratory	Respiratory Wear appropriate respirator when ventilation is inadequate.	
Hands Rubber gloves.		

Protective Clothing (Pictograms)



**2-Butoxyethanol** TWA: 25 (ppm) **Exposure Limits** 

TWA: 50 (ppm) from OSHA (PEL)

Monoethanolamine

TWA: 3 (ppm)
TWA: 6 (ppm) from OSHA (PEL)
STEL: 6 (ppm)

Consult local authorities for acceptable exposure limits.

Section 9. Physica	Section 9. Physical and Chemical Properties				
Physical State and Appearance	Liquid.	Odor	Lemon like.		
Molecular Weight	Not applicable.	Taste	Not available.		
pН	11.8 to 12.8 [Basic.]	Color	Pale Green.		
Boiling/Condensation Point	214°F initial				
Melting/Freezing Point	Not available.				
Critical Temperature	Not available.				
<b>Instability Temperature</b>	Not available.				
Specific Gravity	1 (Water = 1)				
Vapor Pressure	20mm Hg @ 68°F				
Vapor Density	>1 (Air = 1)				
Volatility	95	95			
VOC	23 (%)				
Evaporation Rate	<1 compared to Butyl acetate.				
Dispersion Properties	See solubility in water.				
Solubility	Easily soluble in cold water.				
The Product is:	Non-flammable.				
Auto-ignition Temperature	Not available.				
Flash Points	Not available.				
Flammable Limits	Not available.				
Fire Hazards in Presence of Various Substances	Non-flammable.				

Section 10. Stability and Reactivity Data		
Stability	The product is stable.	
Incompatibility with Various Substances	Strong acids or oxidizers.	
Hazardous Decomposition Products	Will not occur.	

Section 11. Toxico	Section 11. Toxicological Information		
<b>Routes of Entry</b>	Dermal contact. Eye contact. Inhalation. Ingestion.		
Toxicity to Animals	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF 4-HOUR EXPOSURE.  Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol).  Acute toxicity of the gas (LC50): 926 ppm 4 hour(s) [Mouse]. (2-Butoxyethanol).		
Acute Effects on Humans  Eyes	Severe eye irritant. Liquid and mist may damage the eyes causing corneal injury.		
Skin	Corrosive. Skin contact may produce burns.		
Inhalation	Vapors may be irritating to the mucous membranes in the nose, throat, and lungs. High concentrations may cause headache, dizziness, and nausea.		
Ingestion	Irritating to the mouth, throat, and gastrointestinal system. May cause dizziness, headache, nausea, vomiting, and diarrhea. Harmful if swallowed.		
Chronic Effects on Humans	Asthma and related respiratory illness may be aggravated by exposure. Repeated prolonged exposure to the gas can produce lung damage. Repeated or prolonged exposure to the substance can produce kidney damage. Repeated or prolonged exposure to the substance can produce liver damage. Repeated or prolonged exposure to the substance c produce nervous system damage. However, in light of good industrial hygiene, exposure any chemical should be kept to a minimum.		
Special Remarks on Toxicity to Animals	No additional remark.		
Special Remarks on Chronic Effects on Humans	No additional remark.		

Section 12. Ecolog	gical Information
Ecotoxicity	Not available.
BOD5 and COD	Not available.
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.
Toxicity of the Products of Biodegradation	Not available.
Special Remarks on the Products of Biodegradation	No additional remark.

# Section 13. Disposal Considerations Waste Information Waste must be disposed of in accordance with federal, state and local environmental control regulations. Waste Stream Not available.

# Section 14. Transport Information

DOT (U.S.A) (Pictograms)



TDG Classification 8



PIN UN, Proper Shipping Shipping name: Corrosive liquids n.o.s. UNNA: 1760 PG: II

Name, PG

Maritime Transportation Not available.

**Special Provisions for** 

**Transport** 

Not available.


International


**Regulations Lists** 

WHMIS (Classification)	WHMIS Class E: Corrosive liquid. WHMIS CLASS D-2: Material causing other toxic effects.				
Regulatory Lists	No products were found.				
Other Regulations	OSHA: Hazardou	ous by definition of Hazard Communication Standard (29 CFR 1910.1200).			
Other Classifications	HCS (U.S.A.)	HCS Class: Corrosive liquid.  California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Ethylene Oxid 1 ppm California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Ethylene Oxide < 1ppm			
	USA Regulatory Lists				
Massachusetts RTK: Ethylene Oxide SARA 311/312 MSDS distribution - chemical ir identification: 2-Butoxyethanol: immediate heal hazard SARA 313 toxic chemical notification and relea		chemical inventory - hazard ediate health hazard, delayed health			
	DSD (EEC)	R22- Harmful if swallowed. R36/38- Irritating to eyes and skin.			

No products were found.

Hazardous Material Information System (U.S.A.)





The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product.

Specific Hazard

## Section 16. Other Information

Validated by CRushton on 1/18/2005.

Verified by CRushton. Printed 1/18/2005.

**Information Contact Betco Corporation** 

1001 Brown Avenue Toledo, Ohio 43607

### Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 1/18/2005. Extreme Page: 6/6

Continued on Next Page