



Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200

| | | |
|--------------------|---|----------------------------------|
| | WHMIS Class D-2B: Material causing other toxic effects (TOXIC). | HCS Class: Irritating substance. |
| WHMIS (Pictograms) | WHMIS (Classification) | HCS |

Section 1. Chemical Product and Company Identification

| | | | |
|--------------------------|--|-------------------------|-------------------------|
| Product Name/ Trade name | Furniture Polish | Code | 060 |
| Synonym | Furniture Polish | CAS # | Not applicable. |
| Chemical Family | Not available. | Validation Date | 3/20/2004 |
| Chemical Formula | Not applicable. | Print Date | 3/27/2004 |
| Manufacturer/ Supplier | Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607 (419) 241-2156 | In Case of Emergency | Chemtrec (800) 424-9300 |
| TSCA | TSCA Inventory: All components listed or are exempt from listing. | | |
| DSL/ NDSL | All components listed unless noted elsewhere on this MSDS | | |
| | | Protective Clothing | |

Section 2. Composition and Information on Ingredients

| Name | CAS # | % by Weight | Exposure Limits | LC ₅₀ /LD ₅₀ |
|----------------------------|------------|-------------|---|------------------------------------|
| 1) Liquified Petroleum Gas | 68476-85-7 | 10-15 | TWA: 1000 (ppm) TWA: 1000 (ppm) from OSHA (PEL) [United States] | Not available. |
| 2) Heptane | 142-82-5 | 10-15 | TWA: 400 (ppm) TWA: 500 (ppm) from OSHA (PEL) [United States] | Not available. |
| 3) Mineral Seal Oil | 64742-06-9 | <2 | STEL: 500 (ppm) TWA: 100 (ppm) TWA: 100 (ppm) from OSHA (PEL) [United States] | Not available. |
| 4) Perfume Oil | 8007-02-1 | <2 | Not available. | Not available. |

Section 3. Hazards Identification

| | |
|----------------------------------|---|
| Potential Acute Health Effects | This product is an eye irritant. |
| Potential Chronic Health Effects | Repeated skin exposure can produce local skin destruction, or dermatitis. |
| Carcinogenic Effects | Not classified or listed by IARC, NTP, OSHA, EU and ACGIH. |

Section 4. First Aid Measures

| | |
|--------------|--|
| Eye Contact | Flush with large quantities of water. Seek medical attention if irritation occurs. |
| Skin Contact | Flush with water. Seek medical attention if irritation occurs. |
| Inhalation | N/A |
| Ingestion | Dilute with two glasses of water. Seek medical attention if symptoms persist. |

Section 5. Fire Fighting Measures

| | |
|--------------------------------------|--------------------------|
| Products of Combustion | Not available. |
| Fire Fighting Media and Instructions | CO2, dry chemical, foam. |
| Special Remarks on Fire Hazards | N/A |
| Special Remarks on Explosion Hazards | Heated cans may burst. |

Section 6. Accidental Release Measures

| | |
|--|---|
| Small Spill and Leak | N/A. |
| Large Spill and Leak | Absorb with an inert material and put the spilled material in an appropriate waste disposal. |
| Personal Protection in Case of a Large Spill | Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product. |

Section 7. Handling and Storage

| | |
|-----------------|---|
| Precautions | Avoid contact with skin and eyes. Keep away from heat. Keep away from sources of ignition. |
| Incompatibility | None known. |
| Storage | Combustible materials should be stored away from extreme heat and away from strong oxidizing agents. Keep out of the reach of children. Not for use or storage in or around the home. |

Section 8. Exposure Controls/Personal Protection

Engineering Controls Good general ventilation should be sufficient to control airborne levels.

Personal Protection

Eyes Safety glasses.

Body No special protective clothing is required.

Respiratory Wear appropriate respirator when ventilation is inadequate.

Hands Gloves.

Protective Clothing (Pictograms)



Exposure Limits

Liquified Petroleum Gas

TWA: 1000 (ppm)

TWA: 1000 (ppm) from OSHA (PEL)

Heptane

TWA: 400 (ppm)

TWA: 500 (ppm) from OSHA (PEL)

STEL: 500 (ppm)

Mineral Seal Oil

TWA: 100 (ppm)
TWA: 100 (ppm) from OSHA (PEL)

Petroleum Distillates

TWA: 5 (mg/m³)
TWA: 5 (mg/m³) from OSHA (PEL)

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

| | | | |
|--|---|--------------|----------------|
| Physical State and Appearance | Liquid. | Odor | Lemon like. |
| Molecular Weight | Not applicable. | Taste | Not available. |
| pH | 10 to 11 [Basic.] | Color | Clear White. |
| Boiling/Condensation Point | N/A | | |
| Melting/Freezing Point | Not available. | | |
| Critical Temperature | Not available. | | |
| Instability Temperature | Not available. | | |
| Specific Gravity | Not available. | | |
| Vapor Pressure | 55 psig @ 68°F | | |
| Vapor Density | >1 (Air = 1) | | |
| Volatility | 85 | | |
| VOC | 257.43 (g/l). | | |
| Evaporation Rate | <1 | | |
| | | | |
| | | | |
| Dispersion Properties | Not available. | | |
| Solubility | Not available. | | |
| The Product is: | Non-flammable. | | |
| Auto-ignition Temperature | Not available. | | |
| Flash Points | NO FLAME OR FLASH BACK PER CPSC FLAME PROJECTION TEST. | | |
| Flammable Limits | LOWER: 0.9% UPPER: 9.5% | | |
| Fire Hazards in Presence of Various Substances | No specific information is available in our database regarding the flammability of this product in presence of various materials. | | |
| Explosion Hazards in Presence of Various Substances | Containers may explode when heated. | | |

Section 10. Stability and Reactivity Data

| | |
|--|------------------------|
| Stability | The product is stable. |
| Incompatibility with Various Substances | None known. |
| Hazardous Decomposition Products | Will not occur. |

Section 11. Toxicological Information

| | |
|--|---|
| Routes of Entry | Skin contact. INHALATION Eye Contact |
| Toxicity to Animals | Acute oral toxicity (LD50): 4000 mg/kg [Rat]. (Triethanolamine). |
| Acute Effects on Humans | |
| <i>Eyes</i> | Eye irritant. May cause redness and swelling of the conjunctiva. |
| <i>Skin</i> | Defatting to skin on repeated contact. |
| <i>Inhalation</i> | N/A |
| <i>Ingestion</i> | May be irritating to the gastrointestinal system. Nausea, vomiting, and diarrhea expected with large doses. |
| Chronic Effects on Humans | Repeated skin exposure can produce local skin destruction, or dermatitis. |
| Special Remarks on Toxicity to Animals | No additional remark. |
| Special Remarks on Chronic Effects on Humans | No additional remark. |



Section 12. Ecological Information

| | |
|---|---|
| Ecotoxicity | Not Available |
| BOD5 and COD | Not available. |
| Products of Biodegradation | Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise. |
| Toxicity of the Products of Biodegradation | Not available. |
| Special Remarks on the Products of Biodegradation | No additional remark. |


Section 13. Disposal Considerations

| | |
|-------------------|--|
| Waste Information | Waste must be disposed of in accordance with federal, state and local environmental control regulations. |
| Waste Stream | Not available. |

Section 14. Transport Information

| | | |
|----------------------------------|---|---|
| DOT (U.S.A) (Pictograms) |  | |
| TDG Classification | Not controlled under TDG (Canada). |  |
| PIN UN, Proper Shipping Name, PG | Not applicable. | |
| Maritime Transportation | Not available. | |
| Special Provisions for Transport | Not applicable. | |

Section 15. Other Regulatory Information and Pictograms

WHMIS (Classification) WHMIS Class D-2B: Material causing other toxic effects (TOXIC). 

Regulatory Lists No products were found.

Other Regulations Not available. or of its ingredients


Other Classifications

| | |
|--|---|
| HCS (U.S.A.) | HCS Class: Irritating substance. |
| USA Regulatory Lists | SARA 311/312 MSDS distribution - chemical inventory - hazard identification: Liquified Petroleum Gas: fire |
| DSD (EEC) | This product is not classified according to the EU regulations. |
| International Regulations Lists | No products were found. |

Hazardous Material Information System (U.S.A.)

| | |
|-----------------|---|
| Health | 1 |
| Flammability | 1 |
| Physical Hazard | 0 |

National Fire Protection Association (U.S.A.)



The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product.

Section 16. Other Information

Validated by CRushton on 3/20/2004.

Verified by CRushton.
Printed 3/27/2004.

Information Contact Betco Corporation
1001 Brown Avenue
Toledo, Ohio 43607

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.