

Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200



WHMIS Class D-2B: Material causing other toxic effects (TOXIC).

Class: Irritating substance.

WHMIS (Pictograms)

WHMIS (Classification)

HCS

Product Name/ Trade name	Green Earth Floor Stripper	Code	541
Synonym	Floor Stripper	CAS#	Mixture.
Chemical Family		Validation	Date 4/25/2005
Chemical Formula		Print Date	4/25/2005
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Oh 43607 (419) 241-2156	In Case of Emergency	Chemtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS	l e	Protective Clothing







Section 2. Composition and Information on Ingredients				
Name	CAS#	% by Weight	Exposure Limits	LC ₅₀ /LD ₅₀
Benzyl Alcohol Tripropylene Glycol Methyl Ether Sodium Xylene Sulfonate	100-51-6 25498-49-1 1300-72-7	10-15 20-30 1-10	TWA: 3 STEL: 6 (ppm) Not available. Not available.	Not available. Not available. ORAL (LD50): Acute: 650 mg/kg [Rat]. 5939 mg/kg [Mouse].
Alcohol Ethoxylate Alcohols, C12-C14, ethoxylated propoxylated	68439-46-3 68439-51-0	1-5 1-5	Not available. Not available.	Not available. Not available.

Section 3. Hazards Identification

Potential Acute Health Effects

This product is a severe eye irritant. Harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Potential Chronic Health

Over-exposure by inhalation may cause respiratory irritation. Repeated or prolonged

exposure to the substance can produce nervous system damage.

Carcinogenic Effects

Effects

Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First Aid Measures		
Eye Contact	Avoid contact with eyes Flush with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Seek immediate medical attention.	
Skin Contact	Avoid contact with skin and eyes Flush with plenty of water for at least 15 minutes. Seek medical attention.	
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible.	
Ingestion	Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person	

Section 5. Fire Fighting Measures		
Products of Combustion	These products are carbon oxides (CO, CO2).	
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.	
Special Remarks on Fire Hazards	Not available.	
Special Remarks on Explosion Hazards	No additional remark.	

Section 6. Accidental Release Measures		
Small Spill and Leak	Absorb with an inert material and place in an appropriate waste disposal container.	
Large Spill and Leak	Absorb with DRY earth, sand or other non-combustible material. Block the path of any flowing material using soil, gravel, or other readily available material. Eliminate all ignition sources. Prevent entry into sewers, basements or confined areas.	
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product.	

Section 7. Handling and Storage			
Precautions	Avoid contact with skin and eyes Avoid breathing vapors of this product. Keep away from incompatibles. Keep away from sources of ignition. Provide exhaust ventilation or other engeneering controls to keep the airborne concentrations of vapors below their respective threshold limit value.		
Incompatibility	Highly reactive with oxidizing agents, reducing agents. Reactive with metals.		
Storage	Combustible materials should be stored away from extreme heat and away from strong oxidizing agents. Keep out of the reach of children. Not for use or storage in or around the home.		

Section 8. Exposure Controls/Personal Protection			
Engineering Controls	Local exhaust ventilation should be provided.		
Personal Protection Eyes	Splash goggles.		
Body	Disposable outer garments when there is the potential for contact with the material. Boots.		
Respiratory	Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate.		
Hands	Gloves.		

Protective Clothing (Pictograms)









Exposure Limits

Benzyl Alcohol TWA: 3 STEL: 6 (ppm)

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties			
Physical State and Appearance	Liquid.	Odor	Characteristic. (Strong.)
Molecular Weight	Not applicable.	Taste	Not available.
pН	10 to 11 [Basic.]	Color	White.
Boiling/Condensation Point	100°C (212°F)		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.0311 (Water = 1)		
Vapor Pressure	Not available.		
Vapor Density	Not available.		
Volatility	Not available.		
VOC	108 (g/L)		
Evaporation Rate	<1 compared to Butyl acetate.		
Dispersion Properties	See solubility in water.		
Solubility	Partially soluble in cold water, hot water.		
The Product is:	Non-flammable.		
Auto-ignition Temperature	Not available.		
Flash Points	Closed cup: >98.889°C (210°F).		
Flammable Limits	Not available.		
Fire Hazards in Presence of Various Substances	Not available.		
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in prese Risks of explosion of the product in prese		


Section 10. Stability and Reactivity Data		
Stability	The product is stable.	
Incompatibility with Various Substances	Highly reactive with oxidizing agents, reducing agents. Reactive with metals.	
Hazardous Decomposition Products	Not available.	


Section 11. Toxicological Information		
Routes of Entry	Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.	
Toxicity to Animals	Acute oral toxicity (LD50): 650 mg/kg [Rat]. (Sodium Xylene Sulfonate).	
Acute Effects on Humans		
Eyes	Very hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching.	
Skin	Sensitization of the product: Not available. Very hazardous in case of skin contact (irritant, permeator). Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.	
Inhalation	Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Irritating to mouth, throat and stomach.	
Ingestion	Very hazardous in case of ingestion. May be fatal if swallowed. May cause headache, dizziness, nausea, vomiting and diarrhea. May cause labored breathing.	
Chronic Effects on Humans	Over-exposure by inhalation may cause respiratory irritation. Repeated or prolonged exposure to the substance can produce nervous system damage.	
Special Remarks on Toxicity to Animals	Not available.	
Special Remarks on Chronic Effects on Humans	Not available.	

Section 12. Ecological Information		
Ecotoxicity	Not available.	
BOD5 and COD	Not available.	
Products of Biodegradation	These products are carbon oxides (CO, CO2) and water.	
Toxicity of the Products of Biodegradation	The products of degradation are less toxic than the product itself.	
Special Remarks on the Products of Biodegradation	Not available.	

Section 13. Disposal Considerations	
Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Waste Stream	Not available.

DOT (U.S.A) (Pictograms) TDG Classification Not a TDG controlled material. PIN UN, Proper Shipping Not applicable. Name, PG Maritime Transportation Not available. Special Provisions for Not available. Transport





Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Validated on 4/25/2005. Green Earth Floor Stripper Page: 6/6

Continued on Next Page