

Material Safety Data Sheet This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200



CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
CLASS D-1A: Material causing immediate and serious toxic effects

(VERY TOXIC).

Class: Irritating substance.

Class: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C

WHMIS (Pictograms)

WHMIS (Classification)

HCS

Section 1. Chemical Product and Company Identification			
Product Name/ Trade name	Scorch Plus RTU	Code	351
Synonym	Vegetation Killer	CAS#	Mixture.
Chemical Family	Not available.	Validation Da	ate 3/26/2004
Chemical Formula	Not applicable.	Print Date	3/27/2004
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Oh 43607 (419) 241-2156	In Case of Emergency	Chemtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS	-	Protective Clothing

Section 2. Composition and Information on Ingredients				
Name	CAS#	% by Weight	Exposure Limits	$ ext{LC}_{50}/ ext{LD}_{50}$
1) Aliphatic Hydrocarbon Mixture	8008-20-6	0-100	TWA: 100 (ppm) TWA: 100 (ppm) from OSHA (PEL) [United States]	Not available.
2) Prometon: 2,4-Bis (isopropylamino)-6-Methoxy-S-Triazine	1610-18-0	1.5	Not available.	Not available.
3) 2-Butoxyethanol	111-76-2	0-5	TWA: 20 (ppm) from ACGIH (TLV) [United States] TWA: 50 (ppm) from OSHA (PEL) [United States]	ORAL (LD50): Acute: 1746 mg/kg [Rat].

Section 3. Hazards Id	lentification
Potential Acute Health Effects	Very hazardous in case of eye contact (irritant), of ingestion. Hazardous in case of skin contact (irritant, permeator), . Non-corrosive for skin. Non-sensitizer for skin. Non-corrosive to the eyes. Non-corrosive for lungs. Inflammation of the eye is characterized by redness, watering, and itching.
Potential Chronic Health Effects	Over-exposure by inhalation may cause respiratory irritation.
Carcinogenic Effects	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First	t Aid Measures
Eye Contact	Check for and remove any contact lenses. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact	Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.
Inhalation	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
Ingestion	Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Section 5. Fire Fighting Measures	
Products of Combustion	Not available.
Fire Fighting Media and Instructions	Use dry chemical or CO2.
Special Remarks on Fire Hazards	Avoid use of water streams.
Special Remarks on Explosion Hazards	Drums heated by a fire can explode.

Section 6. Accidental Release Measures		
Small Spill and Leak	Safety glasses.	
Large Spill and Leak	Absorb with DRY earth, sand or other non-combustible material. Prevent entry into sewers, basements or confined areas; dike if needed.	
	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.	

Section 7. Hand	lling and Storage
Precautions	Keep locked up Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapor/spray. In case of insufficient ventilation, wear suitable respiratory equipment. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes
Incompatibility	oxidizing agents
Storage	Combustible materials should be stored away from extreme heat and away from strong oxidizing agents. Keep out of the reach of children. Not for use or storage in or around the home.

Section 8. Exposure (Controls/Personal Protection
Engineering Controls	Good general ventilation should be sufficient to control airborne levels.
Personal Protection Eyes	Face shield.
Body	Wear overalls or long sleeved shirt and long trousers, nitrile rubber or neoprene gloves, rubber boots.
Respiratory	Wear appropriate respirator when ventilation is inadequate.
Hands	Gloves (impervious).
Protective Clothing (Pictograms)	

Exposure Limits Aliphatic Hydrocarbon Mixture

TWA: 100 (ppm)
TWA: 100 (ppm) from OSHA (PEL) [United States]

2-Butoxyethanol

TWA: 20 (ppm) from ACGIH (TLV) [United States]
TWA: 50 (ppm) from OSHA (PEL) [United States]

Consult local authorities for acceptable exposure limits.

Section 9. Physical a	and Chemical Properties		
Physical State and Appearance	Liquid.	Odor	Characteristic.
Molecular Weight	Not applicable.	Taste	
pН	Not available.	Color	Brown.
Boiling/Condensation Point	350°F initial		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	0.82 (Water = 1)		
Vapor Pressure	<10mm Hg @ 68°F		
Vapor Density	>1 (Air = 1)		
Volatility	90		
VOC	Not available.		
Evaporation Rate	<1		
Dispersion Properties	Not available.		
Solubility	Not available.		
The Product is:	Flammable.		
Auto-ignition Temperature	Not available.		
Flash Points	CLOSED CUP: 45.7778°C (114.4°F).		
Flammable Limits	LOWER: 1% UPPER: 6%		
Fire Hazards in Presence of Various Substances	Not available.		
Explosion Hazards in Presence of Various Substances	Explosive in presence of open flames and spar	rks, of heat.	

Section 10. Stability and Reactivity Data	
Stability	The product is stable.
Incompatibility with Various Substances	oxidizing agents
Hazardous Decomposition Products	Will not occur.

Section 11. Toxicolog	gical Information
Routes of Entry	Absorbed through skin. Dermal contact. Eye contact. Inhalation. Ingestion.
Toxicity to Animals	Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol).
Acute Effects on Humans	
Eyes	Very hazardous in case of eye contact (irritant). Inflammation of the eye is characterized by redness, watering, and itching.
Skin	Hazardous in case of skin contact (irritant, permeator). Non-sensitizer for skin. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering. Harmful if absorbed through the skin.
Inhalation	Hazardous in case of inhalation.
Ingestion	Aspiration hazard if swallowed- can enter lungs and cause damage.
Chronic Effects on Humans	Over-exposure by inhalation may cause respiratory irritation.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Not available.

Section 12. Ecologic	Section 12. Ecological Information	
Ecotoxicity	Not available.	
BOD5 and COD	Not available.	
Products of Biodegradation	Not available.	
Toxicity of the Products of Biodegradation	Not available.	
Special Remarks on the Products of Biodegradation	Not available.	

Section 13. Disposal Considerations		
Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.	
Waste Stream	Not available.	

Section 14. Transport Information

DOT (U.S.A) (Pictograms)



TDG Classification Class 3: Flammable liquid.



PIN UN, Proper Shipping Name, PG

Shipping name: FLAMMABLE LIQUIDS, N.O.S. UNNA: UN1993 PG: III

Maritime Transportation

Not available.

Not available.

Section 15. Other R	Regulatory Informa	ation and Pictograms	
WHMIS (Classification)	CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F). CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC).		
Regulatory Lists	No products were found.		
Other Regulations	OSHA: Hazardous	by definition of Hazard Communication Standard (29 CFR 1910.1200).	
Other Classifications	HCS (U.S.A.)	Class: Irritating substance. Class: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F).	
	USA Regulatory Lists		
		SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Butoxyethanol: immediate health hazard, delayed health hazard SARA 313 toxic chemical notification and release reporting: 2-Butoxyethanol	
	DSD (EEC)	R10- Flammable.	
	International Regulations Lists	No products were found.	
Hazardous Material Information System (U.S.A.)	Health Flammability Physical Hazard	3 National Fire Protection Association (U.S.A.) Health Flammability Instability	
		ovide only a quick reference for hazard information. The ENTIRE Specific Hazard rds, First Aid measures, and PPE associated with this product.	

Validated by CRushton on 3/26/2004.		Verified by CRushton.
•		Printed 3/27/2004.
Information Contact	Betco Corporation 1001 Brown Avenue Toledo, Ohio 43607	
Notice to Reader		

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although

certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Page: 5/5 Validated on 3/26/2004. Scorch Plus RTU

Continued on Next Page