




Material Safety Data Sheet

This MSDS is prepared in accordance with OSHA 29 CFR 1910.1200

	WHMIS CLASS E: Corrosive liquid.	.HCS CLASS: Corrosive liquid.
WHMIS (Pictograms)	WHMIS (Classification)	HCS

Section 1. Chemical Product and Company Identification

Product Name/ Trade name	Ultra 2000	Code	136
Synonym	Super Double Strength Degreaser	CAS #	Not applicable.
Chemical Family	Not available.	Validation Date	3/20/2004
Chemical Formula	Not applicable.	Print Date	3/27/2004
Manufacturer/ Supplier	Betco Corporation 1001 Brown Avenue Toledo, Oh 43607 (419) 241-2156	In Case of Emergency	Chemtrec (800) 424-9300
TSCA	TSCA Inventory: All components listed or are exempt from listing.		
DSL/ NDSL	All components listed unless noted elsewhere on this MSDS		
		Protective Clothing 	

Section 2. Composition and Information on Ingredients

Name	CAS #	% by Weight	Exposure Limits	LC ₅₀ /LD ₅₀
1) 2-Butoxyethanol	111-76-2	5-10	TWA: 20 (ppm) from ACGIH (TLV) [United States] TWA: 50 (ppm) from OSHA (PEL) [United States]	ORAL (LD50): Acute: 1746 mg/kg [Rat].
2) Potassium Metasilicate	1312-76-1	5-10	Not available.	Not available.
3) Sodium Metasilicate	6834-92-0	1-5	Not available.	Not available.
4) Sodium Xylene Sulfonate	1300-72-7	5-10	Not available.	ORAL (LD50): Acute: 650 mg/kg [Rat]. 5939 mg/kg [Mouse].
5) Potassium Hydroxide	1310-58-3	0-5	Not available.	Not available.
6) Anionic Surfactant	25155-30-0	0-5	Not available.	Not available.
7) Nonionic Surfactant	9016-45-9	<2	Not available.	Not available.

Section 3. Hazards Identification

Potential Acute Health Effects	Corrosive to skin and eyes on contact. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath.
Potential Chronic Health Effects	Repeated or prolonged exposure to the substance can produce blood disorders. Repeated or prolonged exposure to the substance can produce kidney damage. Repeated or prolonged exposure to the substance can produce liver damage. Repeated or prolonged exposure to the substance can produce nervous system damage.
Carcinogenic Effects	Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

Section 4. First Aid Measures

Eye Contact	Hold eye open and rinse slowly and thoroughly with water for 15 to 20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor immediately for treatment advice.
Skin Contact	Rinse skin with plenty of water for 15 to 20 minutes. Call a poison control center or doctor for further treatment advice.
Inhalation	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration., preferably mouth to mouth if possible. Call a poison control center or doctor for further treatment advice.
Ingestion	Call a poison control center immediately for treatment advice. Have person sip a glass of water if able to swallow. Do NOT induce vomiting unless instructed to do so by a poison control center or doctor. Do not give anything by mouth to an unconscious person

Section 5. Fire Fighting Measures

Products of Combustion	Not available.
Fire Fighting Media and Instructions	Non-flammable substance.
Special Remarks on Fire Hazards	No additional remark.
Special Remarks on Explosion Hazards	No additional remark.


Section 6. Accidental Release Measures

Small Spill and Leak	Absorb with an inert material and place in an appropriate waste disposal container.
Large Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Personal Protection in Case of a Large Spill	Splash goggles. Full suit. Boots. Gloves. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Section 7. Handling and Storage

Precautions	After handling, always wash hands thoroughly with soap and water. Avoid contact with skin and eyes.
Incompatibility	Strong acids. acids
Storage	Corrosive materials should be stored in a separate safety storage cabinet or room. Keep out of reach of children. For Institutional and Commercial Use

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels.
Personal Protection	
<i>Eyes</i>	Splash goggles.
<i>Body</i>	Long Pants and Long Sleeves to avoid skin contact. No additional special protective clothing is required.
<i>Respiratory</i>	Wear appropriate respirator when ventilation is inadequate.
<i>Hands</i>	Gloves (impervious).
Protective Clothing (Pictograms)	

Exposure Limits**2-Butoxyethanol**

TWA: 25 (ppm)

TWA: 50 (ppm) from OSHA (PEL)

Consult local authorities for acceptable exposure limits.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.	Odor	Characteristic.
Molecular Weight	Not applicable.	Taste	Not available.
pH	13.0 - 13.9 [Basic.]	Color	Green.
Boiling/Condensation Point	215°F initial		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Specific Gravity	1.08 (Water = 1)		
Vapor Pressure	20mm Hg @ 68°F		
Vapor Density	>1 (Air = 1)		
Volatility	80		
VOC	Not available.		
Evaporation Rate	<1 compared to Water		
Dispersion Properties	See solubility in water.		
Solubility	Easily soluble in cold water.		
The Product is:	May be combustible at high temperature.		
Auto-ignition Temperature	Not available.		
Flash Points	CLOSED CUP: >98.889°C (210°F).		
Flammable Limits	Not available.		
Fire Hazards in Presence of Various Substances	No specific information is available in our database regarding the flammability of this product in presence of various materials.		
Explosion Hazards in Presence of Various Substances	Not applicable		

Section 10. Stability and Reactivity Data

Stability	The product is stable.
Incompatibility with Various Substances	Strong acids. acids
Hazardous Decomposition Products	Not available.

Section 11. Toxicological Information

Routes of Entry	Eye Contact Ingestion. INHALATION Skin contact.
Toxicity to Animals	WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 1746 mg/kg [Rat]. (2-Butoxyethanol). Acute toxicity of the gas (LC50): 926 ppm 4 hour(s) [Mouse]. (2-Butoxyethanol).
Acute Effects on Humans	<i>Eyes</i> Corrosive to skin and eyes on contact. Eye contact can result in corneal damage . <i>Skin</i> Skin contact may produce burns. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering. <i>Inhalation</i> Harmful if inhaled. <i>Ingestion</i> Irritating to mouth, throat and stomach. May cause headache, dizziness, nausea, vomiting and diarrhea.
Chronic Effects on Humans	Repeated or prolonged exposure to the substance can produce blood disorders. Repeated or prolonged exposure to the substance can produce kidney damage. Repeated or prolonged exposure to the substance can produce liver damage. Repeated or prolonged exposure to the substance can produce nervous system damage.
Special Remarks on Toxicity to Animals	No additional remark.
Special Remarks on Chronic Effects on Humans	No additional remark.



Section 12. Ecological Information

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Products of Biodegradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.
Toxicity of the Products of Biodegradation	Not available.
Special Remarks on the Products of Biodegradation	No additional remark.

Section 13. Disposal Considerations

Waste Information	Waste must be disposed of in accordance with federal, state and local environmental control regulations.
Waste Stream	Not available.

Section 14. Transport Information

DOT (U.S.A) (Pictograms)		
TDG Classification	8	
PIN UN, Proper Shipping Name, PG	Shipping name: Corrosive liquids n.o.s. UNNA: 1760 PG: II	

Maritime Transportation Not available.

Special Provisions for Transport Not available.

Section 15. Other Regulatory Information and Pictograms

WHMIS (Classification) WHMIS CLASS E: Corrosive liquid.



Regulatory Lists SARA 313; 2-Butoxyethanol


Other Regulations OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications	HCS (U.S.A.)	.HCS CLASS: Corrosive liquid.
	USA Regulatory Lists	California prop. 65: This product contains the following ingredients for which the State of California has found to cause reproductive harm (female) which would require a warning under the statute: Ethylene Oxide < 1ppm California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: Ethylene Oxide <1 ppm Massachusetts RTK: Ethylene Oxide SARA 311/312 MSDS distribution - chemical inventory - hazard identification: 2-Butoxyethanol: immediate health hazard, delayed health hazard; Potassium Hydroxide: immediate health hazard SARA 313 toxic chemical notification and release reporting: 2-Butoxyethanol
	DSD (EEC)	R35- Causes severe burns.
	International Regulations Lists	No products were found.

Hazardous Material Information System (U.S.A.)

Health	*	3
Flammability		0
Physical Hazard		0

National Fire Protection Association (U.S.A.)



The Hazard Ranking systems presented on this MSDS provide only a quick reference for hazard information. The ENTIRE MSDS must be consulted to determine any specific hazards, First Aid measures, and PPE associated with this product.

Section 16. Other Information

Validated by CRushton on 3/20/2004.

Verified by CRushton.

Printed 3/27/2004.

Information Contact Betco Corporation
1001 Brown Avenue
Toledo, Ohio 43607

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Continued on Next Page