

## **Buckeye International, Inc.**

2700 Wagner Place Maryland Heights, MO 63043 314/291-1900 **N. F. P. A.**4 = Extreme
3 = High
2 = Moderate
1 = Slight

 $0 = \\ In significant$ 

凸	HEALTH	0
Ø.	FIRE	0
K.3	REACTIVITY	0

## **Material Safety Data Sheet**

24 Hour Medical Emergency Telephone Number: 1-800-303-0441. Outside North America call: 651-632-8956. 24 Hour Transportation Emergency Telephone Number: 1-800-535-5053. Outside North America call: 352-323-3500.

	ON I - IDEN'	TIFICATIO	)N				
PRODUCT	NAME					DATE PREPARED	
BUCKEYE CASTLEGUARD						April 1, 2005	
CHEMICA	L FAMILY					CODE	
Floor Finish, Water Based						5125	
PROPER D			,			<u>l</u>	
SHIPPING	NAME	Compound.	Polishing or Wax	. Liauid			
D.O.T. HA		<u> </u>	8	, 1			
CLASSIFIC	CATION	None					
			AND IDENTITY	'INFORMA'	TION		
% By WGT		MATERIAL	THIND IDENTIFIE	PEL	T.L.V.	C.A.S. NO.	
4.7 Diethylene Glycol Ethyl Ether *			*	NE NE	NE	111-90-0	
>24.3 Soft Water				NE NE	NE NE	7732-18-5	
<50.0 Acrylic Emulsion				NE	NE	25987-66-0	
<10.0	Ethylene Copoly		l	NE	NE	25212-83-3	
<7.0	Acrylate Copoly	mer		NE	NE	63744-68-3	
< 2.0	Tributoxyethyl l	Phosphate		NE	NE	78-51-3	
< 2.0	Perfume, colorii	ng and additive	s less than 1%	NA	NA	NA	
			13 REPORTABLES. ALL 1	INGREDIENTS ARI	E ON TSCA INVEN	VTORY.	
SECTIC BOILING I BOLUBILI VOLATI SPECIFIC ( APPEARA	POINT'F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR	SICAL DA		pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO	UTION) RTU RATE (Water=1)	NTORY. $8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid	
SECTIO BOILING I SOLUBILI VOLATI SPECIFIC APPEARA SECTIO	POINT'F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR	White E AND EXP	212°F Miscible 75.0 1.03 e Opaque Solution, S	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO	UTION) RTU RATE (Water=1)	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid	
SECTION BOILING HE SOLUBILING WOLATE SPECIFIC SAPPEARA SECTION FLASH PO	POINT - PHY POINT F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR	White E AND EXP	212°F Miscible 75.0 1.03 e Opaque Solution, SPLOSION DATA	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO	UTION) RTU RATE (Water=1) DRM FLAMMABI	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid	
SECTION BOILING HE SOLUBILITY WOLATE SPECIFIC APPEARA SECTION FLASH POEXTINGUI	POINT'F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIRI DINT(Test Method)	White E AND EXP	212°F Miscible 75.0 1.03 e Opaque Solution, Se PLOSION DATA Closed Cup: None! NA	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO weet Polymer	UTION) RTU RATE (Water=1) DRM FLAMMABI	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid	
SECTIO BOILING I BOLUBILI 6 VOLATI BPECIFIC APPEARA SECTIO FLASH PO EXTINGUI PECIAL FI	POINT'F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIR DINT(Test Method) ISHING MEDIA	White E AND EXP	212°F Miscible 75.0 1.03 e Opaque Solution, Se PLOSION DATA Closed Cup: None! NA	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO weet Polymer  UPPER LIMIT None	UTION) RTU RATE (Water=1) DRM  FLAMMABI Γ: NA	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid  LE LIMITS  LOWER LIMIT: NA	
SECTIO BOILING H SOLUBILI 6 VOLATI SPECIFIC APPEARA SECTIO FLASH PO EXTINGUI SPECIAL FII	POINT - PHY POINT F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR DN IV - FIRI DINT(Test Method) ISHING MEDIA RE FIGHTING PROC	White E AND EXP Tag EDURES ON HAZARDS	212°F Miscible 75.0 1.03 e Opaque Solution, S PLOSION DATA Closed Cup: None! NA	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO weet Polymer  UPPER LIMIT	UTION) RTU RATE (Water=1) DRM  FLAMMABI Γ: NA	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid  LE LIMITS  LOWER LIMIT: NA	
SECTIO BOILING I BOLUBILI 6 VOLATI 6 PECIFIC APPEARA SECTIO FLASH PO EXTINGUI DIPECIAL FIL JNUSUAL I	POINT - PHY POINT F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIRE DINT(Test Method) ISHING MEDIA RE FIGHTING PROCE	White E AND EXP Tag EDURES ON HAZARDS	212°F Miscible 75.0 1.03 e Opaque Solution, S PLOSION DATA Closed Cup: None! NA	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO weet Polymer  UPPER LIMIT None	UTION) RTU RATE (Water=1) DRM  FLAMMABI Γ: NA	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid  LE LIMITS  LOWER LIMIT: NA	
SECTION BOILING HE SOLUBILITY OF VOLATION FOR SECTION FROM THE SECTION FLASH POPECIAL FITTER SECTION FLASH POPECIAL FLASH POPE	POINT - PHY POINT F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIRI DINT(Test Method) ISHING MEDIA RE FIGHTING PROCE FIRE AND EXPLOSION ON V - REACY	White E AND EXP Tag EDURES  ON HAZARDS  CTIVITY D Stabl	212°F Miscible 75.0 1.03 e Opaque Solution, S PLOSION DATA Closed Cup: None! NA	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO weet Polymer  UPPER LIMIT None	UTION) RTU RATE (Water=1) DRM  FLAMMABI Γ: NA	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid  LE LIMITS  LOWER LIMIT: NA	
SECTION BOILING IN SOLUBILITY OF APPEARA SECTION SECTION SPECIAL FIT SECTION S	PON III - PHY POINT F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIRI DINT(Test Method) ISHING MEDIA RE FIGHTING PROC FIRE AND EXPLOSION ON V - REACY ONS TO AVOID	White E AND EXP Tag EDURES ON HAZARDS  CTIVITY D Stabl None	212°F Miscible 75.0 1.03 e Opaque Solution, S PLOSION DATA Closed Cup: None! NA	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO weet Polymer  UPPER LIMIT None  Products of comboxides of phospi	UTION) RTU RATE (Water=1) DRM  FLAMMABI Γ: NA	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid  LE LIMITS  LOWER LIMIT: NA	
BECTIC BOILING H BOLUBILIT VOLATI SPECIFIC APPEARA SECTIC FLASH PO EXTINGUI SPECIAL FI  JNUSUAL H SECTIC STABILIT CONDITIC NCOMPA	POINT - PHY POINT F TY IN WATER ILE BY WEIGHT GRAVITY NCE AND ODOR ON IV - FIRI DINT(Test Method) ISHING MEDIA RE FIGHTING PROCE FIRE AND EXPLOSION ON V - REACY	White E AND EXP Tag EDURES  ON HAZARDS  CTIVITY D Stabl None Acids	212°F Miscible 75.0 1.03 e Opaque Solution, S PLOSION DATA Closed Cup: None! NA  ATA e k known. s, strong alkali and he	pH (CONC.) pH (USE DIL) EVAPORATION I PRODUCT FO weet Polymer  UPPER LIMIT None  Products of comboxides of phospi	UTION) RTU RATE (Water=1) DRM  FLAMMABI Γ: NA	$8.0 \pm 0.2$ $8.0 \pm 0.2$ $1.0$ Liquid  LE LIMITS  LOWER LIMIT: NA	

**CODE:** 5125 SECTION VI - HEALTH HAZARD DATA ROUTE(S) OF ENTRY: INHALATION? No SKIN? No INGESTION? No HEALTH HAZARDS (Acute and Chronic) Not irritating to eyes and skin. Not toxic by ingestion. CARCINOGENICITY: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No SIGNS AND SYMPTOMS OF OVEREXPOSURE None known. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE None known. EMERGENCY AND FIRST AID PROCEDURES: For Eyes: Flush with cool water for 15 minutes. If irritation occurs and persists, see physician. For Ingestion: Give two large glasses of water. DO NOT induce vomiting. Call physician. Never give anything by mouth to an unconscious person. SECTION VII - SPILL OR LEAK PROCEDURES SPILL RESPONSE Pick up with mop, wet/dry vac or absorbent material. Wash area with detergent solution followed by a clear water rinse. Allow floor to dry before allowing traffic. WASTE DISPOSAL METHOD Flush to sanitary sewer or send to sanitary landfill, following local, state and federal laws. SECTION VIII - SPECIAL PROTECTION INFORMATION EYE PROTECTION VENTILATION When eye contact may occur, wear safety glasses or chemical splash goggles. Normal room ventilation. SKIN PROTECTION RESPIRATORY PROTECTION Rubber gloves or other impervious gloves.\* None required. OTHER PROTECTION Follow good personal hygiene practices. \* Needed for clean up of spill or for possible prolonged skin contact. SECTION IX - SPECIAL PRECAUTIONS PRECAUTIONS IN KEEP OUT OF REACH OF CHILDREN! HANDLING AND STORAGE Keep container closed when not in use. Keep from freezing! Store at room temperature. Do not store above 110°F. OTHER This product is not regulated under CERCLA or RCRA. PRECAUTIONS Not reportable under SARA Title III, Section 311/312. NA = Not Applicable

Disclaimer of Liability

NE = Not Established

PREPARED BY:

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174, Sept. 1985.

Mark Gindling, Director of Research