

Buckeye International, Inc.

2700 Wagner Place Maryland Heights, MO 63043 314/291-1900


N. F. P. A.

4 = Extreme

3 = High2 = Moderate

1 = Slight

0 = Insignificant



Material Safety Data Sheet

24 Hour Medical Emergency Telephone Number: 1-800-303-0441. Outside North America call: 651-632-8956. 24 Hour Transportation Emergency Telephone Number: 1-800-535-5053. Outside North America call: 352-323-3500.

					DATE PREPARED
I	BUCKEYE SV	VAT NA			April 1, 2005
LY					CODE
Alkaline Floor Finish Strippe				l	5035
P	otassium Hydr	oxide), 8, UN	1760, PG II		
	•				
C	orrosive Mater	ial			
- INGRI	EDIENTS AN	D IDENTITY	INFORMA'	TION	
	MATERIAL		PEL	T.L.V.	C.A.S. NO.
ium Hydrox	ride		NE	2 mg/m^3	1310-58-3
2.7 Potassium Hydroxide5.0 Monoethanolamine					141-43-5
>71.3 Water			NE	NE	7732-18-5
<9.0 Dipropylene Glycol n-Butyl Ether			NE	NE	29911-28-2
<5.0 Benzyl Alcohol			NE	NE	100-51-6
<3.0 Neodecanoic Acid			NE	NE	26896-20-8
<3.0 Linear Alkyl Benzene Sulfonic Acid			NE	NE	68584-22-5
ne, Coloring	g and Additives le	ss than 1%	NA	NA	NA
	A TITLE HI GEG	NA DEDODE A DA		DIENTE A DE ON	L TOO A DAY TENTODAY
		313 REPORTABLE	ES. ALL INGRE	DIENTS ARE ON	TSCA INVENTORY.
		2120E	H (CONC.)		13.1 ± 0.2
BOILING POINT °F					13.1 ± 0.2 12.1 ± 0.2
SOLUBILITY IN WATER % VOLATILE BY WEIGHT			•		1.0
SPECIFIC GRAVITY					Liquid
					Elquio
st Method)	Tag Clos	ed Cup: None!		FLAMMABL	E LIMITS
NGUISHING MEDIA NA		NA	UPPER LIMIT: NA		LOWER LIMIT: NA
HTING PRO	OCEDURES		Wear alkali 1	esistant clothing	
ND EXPLO	SION HAZARDS				•.
DEAC	PIX/I/PX/ IN A /P	Α	Oxides of su	itur, carbon and	nitrogen.
- KEAC		A			
AVOID					
			laaala on aaida		
ĭ	Do not mi	x with chiorine b			
OMDOCITI	ON PRODUCTS		None known		
	A C P INGRI Itum Hydrox ethanolamin Pylene Glyce I Alcohol Scanoic Acid Alkyl Benz The PHYS ARE SAF PHYS F VATER WEIGHT TY ID ODOR FIRE St Method) MEDIA GHTING PRO ND EXPLOS	Alkaline Floor F Corrosive Liquic Potassium Hydro Corrosive Mater INGREDIENTS AND MATERIAL Jum Hydroxide ethanolamine Pylene Glycol n-Butyl Ether I Alcohol ecanoic Acid Alkyl Benzene Sulfonic A	Alkaline Floor Finish Stripper, Corrosive Liquids, n.o.s., (cont Potassium Hydroxide), 8, UN Corrosive Material INGREDIENTS AND IDENTITY MATERIAL Jum Hydroxide ethanolamine Poylene Glycol n-Butyl Ether I Alcohol Exanoic Acid CAlkyl Benzene Sulfonic Acid Ine, Coloring and Additives less than 1% ARE SARA TITLE III SEC 313 REPORTABLE PHYSICAL DATA F 212°F VATER Infinite WEIGHT 94.0 TY 1.02 ID ODOR Slight Floral, Clear Green S I FIRE AND EXPLOSION DATA St Method) Tag Closed Cup: None! MEDIA NA SHTING PROCEDURES ND EXPLOSION HAZARDS - REACTIVITY DATA Stable AVOID None known.	Alkaline Floor Finish Stripper, Water Based Corrosive Liquids, n.o.s., (contains Ethanola Potassium Hydroxide), 8, UN 1760, PG II Corrosive Material - INGREDIENTS AND IDENTITY INFORMA MATERIAL MATERIAL MATERIAL ME Sulan Hydroxide NE NE NE NE NE NE NE NE NE N	Alkaline Floor Finish Stripper, Water Based Corrosive Liquids, n.o.s., (contains Ethanolamine and Potassium Hydroxide), 8, UN 1760, PG II Corrosive Material - INGREDIENTS AND IDENTITY INFORMATION MATERIAL MATERIAL ME ME ME ME ME ME ME ME ME M

CODE: 5035

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION? No SKIN? Yes INGESTION? Yes

HEALTH HAZARDS (Acute and Chronic)

Corrosive. Will cause burns to eyes and skin. Harmful or fatal if swallowed.

CARCINOGENICITY: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

SIGNS AND SYMPTOMS OF OVEREXPOSURE

For Eyes: Redness or burning sensation.

For Skin: Redness of skin or a warming sensation. For Ingestion: Nausea, headache.

MEDICAL CONDITIONS

GENERALLY AGGRAVATED BY EXPOSURE

Dermatitis. Can cause defatting of skin tissue.

EMERGENCY AND FIRST AID PROCEDURES

For Eyes: Flush with cool water for 15 minutes. See physician.

For Skin: Flush with water for 15 minutes. If irritation occurs and persists, see physician.

For Ingestion: Give two large glasses of water. DO NOT induce vomiting. Call physician immediately!

Never give anything by mouth to an unconscious person.

SECTION VII - SPILL OR LEAK PROCEDURES

SPILL RESPONSE

Pick up with mop, wet/dry vac or absorbent material. Rinse area with clear water and allow floor to dry before allowing traffic.

WASTE DISPOSAL

METHOD Flush to sanitary sewer or send to sanitary landfill, following local, state and federal laws.

SECTION VIII - SPECIAL PROTECTION INFORMATION

Wear safety glasses or chemical splash goggles. Normal room ventilation.

SKIN Rubber gloves or other RESPIRATORY

PROTECTION impervious gloves. PROTECTION None required.

OTHER

PROTECTION Wear water or chemical resistant footwear when scrubbing floors.

Follow good personal hygiene practices.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS IN KEEP OUT OF REACH OF CHILDRE

HANDLING AND Store at room temperature.

STORAGE Keep container closed when not in use. Store away from acids.

Store on low shelves. Rinse container before discarding.

OTHER

This product is not regulated under CERCLA. This product is not regulated under RCRA

PRECAUTIONS

NA = Not Applicable

NE = Not Established

This product is not regulated under RCRA
when product label and MSDS spill directions are followed. If more than 10,000 lbs. is
stored in a single day, product may require reporting under SARA Title III, Section

311/312 as an immediate health hazard. Product produced under one or more of the

following U.S. Patents; 5,080,822; 5,080,831; 5,158,710; 5,419,848; 5,585,341 and 5,849,682.

Other patents pending.

PREPARED BY: Mark Gindling, Director of Research

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174, Sept 1985.