



Buckeye International, Inc.
 2700 Wagner Place
 Maryland Heights, MO 63043
 314/291-1900

N. F. P. A.
 4 = Extreme
 3 = High
 2 = Moderate
 1 = Slight
 0 = Insignificant

	HEALTH	1
	FIRE	0
	REACTIVITY	0

Material Safety Data Sheet

24 Hour Medical Emergency Telephone Number: 1-800-303-0441. Outside North America call: 651-632-8956.

24 Hour Transportation Emergency Telephone Number: 1-800-535-5053. Outside North America call: 352-323-3500.

SECTION I - IDENTIFICATION				
PRODUCT NAME BUCKEYE SCAVENGER			DATE PREPARED April 1, 2005	
CHEMICAL FAMILY Malodor Eliminator, Water Based			CODE 5427	
PROPER D.O.T. SHIPPING NAME Compound, Cleaning, Liquid				
D.O.T. HAZARD CLASSIFICATION None				
SECTION II - INGREDIENTS AND IDENTITY INFORMATION				
% By WGT	MATERIAL	PEL	T.L.V.	C.A.S. NO.
>84.0	Soft Water	NE	NE	7732-18-5
<10.0	Nonyl Phenol Ethoxylate	NE	NE	9016-45-9
<5.0	Perfume	NE	NE	Blend
<1.0	Coloring and additives less than 1%	NA	NA	NA
ITEMS MARKED * ARE SARA TITLE III SEC 313 REPORTABLES. ALL INGREDIENTS ARE ON TSCA INVENTORY.				
SECTION III - PHYSICAL DATA				
BOILING POINT °F	212°F	pH (CONC.)	7.6 ± 0.2	
SOLUBILITY IN WATER	Infinite	pH (USE DILUTION) 1:16	9.6 ± 0.2	
% VOLATILE BY WEIGHT	94.0	EVAPORATION RATE (Water=1)	1.0	
SPECIFIC GRAVITY	1.01	PRODUCT FORM	Liquid	
APPEARANCE AND ODOR	Floral, Clear Light Yellow Solution			
SECTION IV - FIRE AND EXPLOSION DATA				
FLASH POINT(Test Method)	Tag Closed Cup: None!	FLAMMABLE LIMITS		
EXTINGUISHING MEDIA	NA	UPPER LIMIT: NA	LOWER LIMIT: NA	
SPECIAL FIRE FIGHTING PROCEDURES	None			
UNUSUAL FIRE AND EXPLOSION HAZARDS	Products of combustion. Oxides of carbon.			
SECTION V - REACTIVITY DATA				
STABILITY	Stable			
CONDITIONS TO AVOID	None known.			
INCOMPATIBILITY	Do not mix with chlorine bleach.			
HAZARDOUS DECOMPOSITION PRODUCTS	None known.			
HAZARDOUS POLYMERIZATION	Will not occur.			

SECTION VI - HEALTH HAZARD DATA			
ROUTE(S) OF ENTRY:	INHALATION? No	SKIN? Yes	INGESTION? No
HEALTH HAZARDS (Acute and Chronic)			
May cause slight eye irritation.			
CARCINOGENICITY:	NTP? No	IARC MONOGRAPHS? No	OSHA REGULATED? No
SIGNS AND SYMPTOMS OF OVEREXPOSURE			
For Eyes: Redness or burning sensation.			
MEDICAL CONDITIONS			
GENERALLY AGGRAVATED BY EXPOSURE			
None known.			
EMERGENCY AND FIRST AID PROCEDURES			
For Eyes: Flush with cool water for 15 minutes. If irritation occurs and persists, see physician.			
For Ingestion: Give two large glasses of water. DO NOT induce vomiting. Call physician.			
Never give anything by mouth to an unconscious person.			
SECTION VII - SPILL OR LEAK PROCEDURES			
SPILL RESPONSE			
Pick up with mop, wet/dry vac or absorbent material. Rinse area with clear water and allow floor to dry before allowing traffic.			
WASTE DISPOSAL			
METHOD	Flush to sanitary sewer or send to sanitary landfill, following local, state and federal laws.		
SECTION VIII - SPECIAL PROTECTION INFORMATION			
EYE PROTECTION	When eye contact may occur	VENTILATION	
	wear safety glasses or chemical splash goggles.		Normal room ventilation.
SKIN PROTECTION	Rubber gloves or other impervious gloves.*	RESPIRATORY PROTECTION	None required.
OTHER PROTECTION	Follow good personal hygiene practices.		
	*Needed for clean up of spill or for possible prolonged skin contact.		
SECTION IX - SPECIAL PRECAUTIONS			
PRECAUTIONS IN HANDLING AND STORAGE	KEEP OUT OF REACH OF CHILDREN! Keep container closed when not in use. Store at room temperature.		
OTHER PRECAUTIONS	This product is not regulated under CERCLA or RCRA. Not reportable under SARA Title III, 311/312.		
NA = Not Applicable NE = Not Established			
PREPARED BY:	Mark Gindling, Director of Research		
Disclaimer of Liability As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174, Sept 1985.			