

# **Buckeye International, Inc.**

2700 Wagner Place Maryland Heights, MO 63043 314/291-1900

## N. F. P. A.


4 = Extreme

3 = High

2 = Moderate

1 = Slight

0 = Insignificant



# **Material Safety Data Sheet**

24 Hour Medical Emergency Telephone Number: 1-800-303-0441. Outside North America call: 651-632-8956. 24 Hour Transportation Emergency Telephone Number: 1-800-535-5053. Outside North America call: 352-323-3500.

	DATE PREPARED April 1, 2005 CODE
	CODE
• 1 1	
. 1 1	5085
isopropanoi and	sodium hydroxide), 3, (8
ATION	
T.L.V.	C.A.S. NO.
NE	90-43-7
NE	120-32-1
NE	80-46-6
400ppm	67-63-0
NE	Blend
NE	7732-18-5
DEDIENTEG A DE ON	L MCCA INIVENIMODA
REDIENTS ARE OF	N TSCA INVENTORY.
	T
	$13.0 \pm 0.2$
	$10.0 \pm 0.2$
	0.9
	Liquid
	nce has no relationship
odor.	
	E LIMITS
MIT: NE	LOWER LIMIT: NE
f combustion	
<del></del>	
vn.	
ccur.	
	NE NE NE 400ppm NE

**CODE: 5085** 

## SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION? Yes SKIN? Yes INGESTION? Yes

HEALTH HAZARDS (Acute and Chronic)

Corrosive. Causes irreversible eye damage and skin burns. Harmful if swallowed, absorbed through skin or inhaled.

CARCINOGENICITY: NTP? No IARC MONOGRAPHS? No OSHA REGULATED? No

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

For Eyes: Redness or burning sensation. For Skin: Redness of skin or a warming sensation.

For Inhalation: Headache. For Ingestion: Headache, nausea.

MEDICAL CONDITIONS

GENERALLY AGGRAVATED BY EXPOSURE

#### Dermatitis.

EMERGENCY AND FIRST AID PROCEDURES Call a poison control center or doctor for treatment advice. If on Clothing: Remove contaminated clothing. For Eyes and Skin: Rinse eyes or skin immediately with plenty of water for 15- 20 minutes. For Inhalation: Remove person to fresh air. For Ingestion: Have person sip a glass of water if able to swallow. DO NOT induce vomiting unless told by a poison control center or doctor. Do not give anything by mouth to an unconscious person. Note to Physician: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsion may be needed.

## SECTION VII - SPILL OR LEAK PROCEDURES

SPILL RESPONSE

Pick up with mop, wet/dry vac or absorbent material. Rinse area with clear water and allow floor to dry before allowing traffic.

WASTE DISPOSAL

Dispose of use solution in sanitary sewer. Contact sewer district before disposing of large amounts of concentrated product. Container disposal - plastic: triple rinse

(or equivalent) then offer for recycling or reconditioning.

## SECTION VIII - SPECIAL PROTECTION INFORMATION

EYE PROTECTION VENTILATION

Wear goggles or safety glasses. Maintain adequate ventilation.

SKIN Wear chemical resistant gloves, long sleeve RESPIRATORY

PROTECTION shirts, pants, socks and shoes. PROTECTION None required.

OTHER

PROTECTION Wash thoroughly with soap and water after handling and before eating, drinking,

or using tobacco.

Remove contaminated clothing and wash before reuse.

## **SECTION IX - SPECIAL PRECAUTIONS**

PRECAUTIONS IN KEEP OUT OF REACH OF CHILDREN!

HANDLING AND STORAGE Do not cut, weld or puncture container.

Do not contaminate water, food or feed by storage or disposal.

OTHER Do not apply this product in a way that will contact workers and other persons, either directly or through drift. Only protected handlers may be in the area during

NA = Not Applicable application.

NE = Not Established If 10,000 pounds is stored in a single day, product may require reporting under SARA Title III, Section 311/312 as an immediate health hazard and fire hazard.

## **PREPARED BY:** Mark Gindling, Director of Research

Disclaimer of Liability

As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of the material. Information contained herein is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof. Conforms to OSHA 174, Sept 1985.