

MATERIAL SAFETY DATA SHEET

SPEEDBALL GLASS Glass and Surface

Date Prepared: 04/10/2001 Date Revised: 04/10/2001 Cleaner

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name/Use: SPEEDBALL GLASS Glass and Surface Cleaner

MANUFACTURER

The Butcher Company 67 Forest Street Marlborough, MA 01752-3012 Butcher Telephone Number: 800-225-9475 Emergency Telephone (24 hours): 800-228-5635 CHEMTREC (U.S./Can.): 800-424-9300 CHEMTREC (Int'l): +1 703-527-3887

2. **COMPOSITION / INFORMATION ON INGREDIENTS**

INGREDIENT(S)	CAS NO.	% BY WEIGHT
Isopropyl alcohol	67-63-0	3 - 5
Propylene glycol n-propyl ether	1569-01-3	1 – 3
Ammonium hydroxide	1336-21-6	0.25 - < 1.0

See Section 8 for Exposure Limits NA - Not Applicable

OSHA REGULATORY STATUS: This product is classified as hazardous under OSHA regulations.

WHMIS CLASS: Class B- Division 3; Class D- Division 2B

HAZARDS IDENTIFICATION 3.

EMERGENCY OVERVIEW

Clear, Blue Liquid. Soapy, ammonia Odor. May Cause Eye Irritation. Combustible.

POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

PRIMARY ROUTE(s) OF EXPOSURE: X Eye X Skin Contact Skin Absorption X Inhalation X Ingestion

EFFECTS OF ACUTE EXPOSURE

EYES:

May cause eye irritation. Symptoms may include redness and pain.

SKIN:

May cause mild skin irritation. Symptoms may include redness.

INHALATION:

High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing, wheezing and shortness of breath. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

MSDS No: 4287 Page: 1 of 7

Date Prepared: 04/10/2001 Date Revised: 04/10/2001

INGESTION:

May cause mouth, throat and stomach irritation. Symptoms may include nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

EFFECTS OF CHRONIC EXPOSURE:

Prolonged or repeated contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

MEDICAL CONDITIONS AGGRAVATED:

May aggravate pre-existing eye, skin and respiratory conditions.

4. FIRST AID MEASURES

EYES:

Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

SKIN:

Flush with water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops.

INHALATION:

Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get medical attention if symptoms persist.

INGESTION:

Do not induce vomiting. Drink large quantities of water. Get immediate medical attention. Never give anything by mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

FLASH POINT AND METHOD: 115°F 46.1°C TCC

FLAMMABLE LIMITS

UPPER EXPLOSIVE LIMIT: 12.7% (2-propanol) LOWER EXPLOSIVE LIMIT: 2% (2-propanol)

AUTOIGNITION TEMPERATURE: Not applicable.

EXTINGUISHING MEDIA:

Use water fog, dry chemical, CO2, or foam.

HAZARDOUS COMBUSTION PRODUCTS:

Normal products of combustion (carbon monoxide and carbon dioxide).

MSDS No: 4287 Page: 2 of 7

Date Prepared: 04/10/2001 Date Revised: 04/10/2001

FIRE AND EXPLOSION HAZARDS:

Class II combustible liquid. This product is combustible and may be ignited by heat, sparks, flame, and other ignition sources. Vapors can travel to a source of ignition and flash back.

FIRE FIGHTING INSTRUCTIONS:

Evacuate area. Cool containers exposed to fire with water. MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Remove ignition sources and ventilate spill area. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop, absorbent and non-sparking tools to collect material for proper disposal. Rinse area with water.

7. HANDLING AND STORAGE

HANDLING:

Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Avoid contact with eyes, skin and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Use spark-proof tools. Wash thoroughly after handling. Remove contaminated clothing. Wash clothing and equipment before reuse.

STORAGE:

Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity). Store away from direct sunlight. Keep away from heat, sparks and flame.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT (PPE)

EYE:

Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

SKIN:

Where prolonged or repeated contact is possible, chemical-resistant clothing (e.g., gloves) is recommended.

RESPIRATORY:

No respiratory protection is required if ventilation is adequate and airborne concentrations are kept below exposure limits. When exposure limits may be exceeded, use appropriate respiratory protection (NIOSH)/MSHA-approved) to prevent overexposure.

ENGINEERING CONTROLS:

Good general room ventilation is expected to be adequate. If user operations generate vapor or mist, ventilation should be used to keep airborne concentrations below exposure limits.

MSDS No: 4287 Page: 3 of 7

Date Prepared: 04/10/2001 Date Revised: 04/10/2001

EXPOSURE LIMITS:

INGREDIENT(S) OSHA PEL/STEL ACGIH TLV/STEL

Isopropyl alcohol 400 ppm (980 mg/m3)/ 400 ppm (983 mg/m3)/ 500 ppm (1225 mg/m3) 500 ppm (1230 mg/m3)

Propylene glycol n-propyl ether NA NA

Ammonium hydroxide 50 ppm (35 mg/m3)/ 25 ppm (17 mg/m3)/ 35 ppm (27 mg/m3) 35 ppm (24 mg/m3)

(NH3)

NA - Not Available

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid ODOR: Soapy, ammonia APPEARANCE: Clear, Blue

pH: 10.5 to 11.5

PERCENT VOLATILE BY WEIGHT: 99.5 VAPOR PRESSURE: Not Available VAPOR DENSITY: Not Available BOILING POINT: Not Available

FREEZING/MELTING POINT: Not Available

SOLUBILITY IN WATER: Complete EVAPORATION RATE: Not Available

SPECIFIC GRAVITY: 1.013 VISCOSITY: Water Thin

OCTANOL/WATER PARTITION COEFFICIENT: Not Available

ODOR THRESHOLD: Not Available

10. STABILITY AND REACTIVITY

STABILITY (CONDITIONS TO AVOID):

Stable.

POLYMERIZATION:

Will not occur.

HAZARDOUS DECOMPOSITION:

None known.

INCOMPATIBLE MATERIALS:

Oxidizers (e.g., bleach) and strong bases (e.g., sodium hydroxide).

11. TOXICOLOGICAL INFORMATION

ACUTE DATA:

Based on testing of a similar product, this product may cause eye irritation; it is not considered to be toxic by inhalation. The following data are available for product ingredients.

MSDS No: 4287 Page: 4 of 7

Date Prepared: 04/10/2001 Date Revised: 04/10/2001

PRODUCT/INGREDIENT	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
Isopropyl alcohol	4710 mg/kg	12870 mg/kg	17000 ppm (4-hr)
Propylene glycol n-propyl ether	2000–4350 mg/kg	3800–4350 mg/kg	Not Available
Ammonium hydroxide	350 mg/kg	Not Available	3670 ppm (4-hr)

SENSITIZATION DATA:

No data available.

CHRONIC DATA:

Prolonged overexposure to isopropyl alcohol by ingestion and inhalation has caused central nervous system effects in humans and laboratory animals; overexposure by ingestion has also caused liver effects in animals. Prolonged overexposure to high concentrations of propylene glycol n-propyl ether by skin absorption, ingestion and inhalation may cause liver, kidney, and central nervous system effects.

REPRODUCTIVE/TERATOGENIC DATA:

Ingestion of isopropyl alcohol has caused slight fetotoxic and reproductive effects in laboratory animals.

CARCINOGENIC/MUTAGENIC DATA:

Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

SYNERGISTIC MATERIALS:

No data available.

12. ECOLOGICAL INFORMATION

This product is made with all biodegradable detergents. No other data available.

13. DISPOSAL CONSIDERATIONS

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA hazardous waste (Ignitable-D001) in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

14. TRANSPORT INFORMATION

DOT/TDG HAZARDOUS MATERIAL DESCRIPTION: Not regulated when in a container of 119 gallons (454 liters) or less.

15. REGULATORY INFORMATION

Not meant to be all-inclusive—selected regulations represented.

MSDS No: 4287 Page: 5 of 7

Date Prepared: 04/10/2001 Date Revised: 04/10/2001

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed, Fire.

313 REPORTABLE INGREDIENTS: Ingredients in this product are not currently subject to notification.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT) CERCLA REGULATORY: Not reportable under CERCLA.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: This product complies with all TSCA inventory requirements.

MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:

INGREDIENT(S)	CAS NO.	STATE LISTING
Water	7732-18-5	Not Listed
Isopropyl alcohol	67-63-0	MA, NJ, PA
Propylene glycol n-propyl ether	1569-01-3	Not Listed

NA - Not Applicable

STATE REGULATIONS: Ammonia is listed on the Massachusetts Right-to-Know Substance List, New Jersey Right-To-Know Hazardous Substance List and the Pennsylvania Hazardous Substance List.

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):


Class B-Division 3, combustible liquid; Class D-Division 2B, eye irritant. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

16. OTHER INFORMATION

HMIS RATING

HEALTH	*	1
FLAMMABILITY		2
REACTIVITY		0
PERSONAL PROTECTION		-

NFPA RATING



MSDS No: 4287 Page: 6 of 7

Date Prepared: 04/10/2001 Date Revised: 04/10/2001

MSDS STATUS

Revision #: 2

This MSDS replaces the May 20, 1998 MSDS. Any changes in information are as follows:

In Section 1

Prepared By Date Prepared [] Print CHEMTREC Phone Number

In Section 9

(Group Field) for Vapor Pressure (Group Field) for Vapor Pressure Density Odor Threshold (Group Field) for Boiling Point (Group Field) for Freezing Point Specific Gravity (From) (Group Field) for Evaporation Rate Coeff Oil/Water

In Section 10

Hazardous Decomposition Products

In Section 15

OSHA Hazard Comm. Rule Regulations: State WHMIS Class

APPROVAL DATE: 04/10/2001

The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.

MSDS No: 4287 Page: 7 of 7