

bursting containers.

Clorox Professional Products Company

1221 Broadway Oakland, CA 94612 Tel. (510) 271-7000

Material Safety Data Sheet

I Product: CLOROX® COMMERCIAL SOLUTIONS™ CLOROX® DISINFECTING SPRAY **Description:** FRAGRANCED AEROSOL **Emergency Telephone Nos.** Other Designations Distributor For Medical Emergencies call: Clorox Professional Products Company EPA Reg. No. 67619-3 (800) 446-1014 1221 Broadway Clorox Disinfecting Spray Oakland, CA 94612 For Transportation Emergencies Chemtrec (800) 424-9300 **II Health Hazard Data III Hazardous Ingredients** EYES: Will cause moderate, reversible eye irritation. Ingredients Concentration Worker Exposure Limit SKIN CONTACT: Will cause minor irritation after prolonged contact. Ethanol 60-80% 1000ppm TLV - TWA Prolonged or frequently repeated skin contact may cause allergic reactions in CAS #64-17-5 some individuals. INGESTION: Low toxicity if ingested. May cause minor irritation of the mouth. 1-5% 1000ppm PEL - TWA Ingestion of large quantities may result in ethanol intoxication. CAS #7409806 (propellant) INHALATION: Intentional misuse by concentrating and inhaling vapors may be harmful or fatal. Inhalation of high concentrations may cause irritation of the Isobutane 5-10% Not Established respiratory tract. Symptoms include headaches, dizziness, nausea, vomiting, CAS #75-28-3 and malaise. MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: None None of the ingredients in this product are on the (ARC, NTP or OSHA carcinogen lists. known. EMERGENCY FIRST AID PROCEDURES: EYES: Immediately flush eyes with plenty of water for at least 15 minutes. If irritation persists, call a physician. TLV\TWA: Threshold Limit Value\Time Weighted Average. SKIN: Wash with plenty of soap and water. IF SWALLOWED: Drink a glass of water. Call a physician. PEL: Permissible Exposure Limit. Source: OSHA **IV Special Protection and Precautions** V Transportation and Regulatory Data No special protection or precautions have been identified for using this product U.S. DOT Hazard Class: ORM - D under directed consumer use conditions. U.S. DOT Proper Shipping Name: Consumer Commodity. The following recommendations are given for production facilities and for other conditions and situations where there is increased potential for accidental, large-EPA - SARA Title III/CERCLA: Bulk product is regulated under sections scale, or prolonged exposure: 311/312. Packaged product is not reportable. Hygienic Practices: Wear safety glasses and protective gloves when handling TSCA Status: All components of this product are on the TSCA inventory. product. Engineering Controls: Use explosion proof ventilation to minimize exposure to vapor or mist. Work Practices: Minimize skin contact and inhalation of vapor or mist. VI Spill Procedures/Waste Disposal VII Reactivity Data Steps to be taken in case material is released or spilled: Eliminate all sources of Stability: Stable ignition. Ventilate area. Mop up excess. Flush off any remaining material with soapy water. Flush again. Respiratory Protection: If handling large industrial or Conditions to Avoid: Temperatures over 120°F warehouse spills, people should use NIOSH approved respiratory protection. Waste Disposal Method: Do not puncture or incinerate (burn) empty or full Incompatibility/Materials to Avoid: Alkalis and acids cans. Dispose of in accordance with state and local regulations for consumer products. Empty cans may be landfilled. <u>Precautions to be taken in Handling and Storage</u>: Do not store above 120^F. Do not puncture or burn. Keep Hazardous Polymerization or Decomposition: None known aerosols from fire or sparks. Store in accordance with NFPA 30B for Level 2 Aerosols. Other Precautions: N/A VIII Fire and Explosion Data **IX Physical Data** Flashpoint: Flashpoint of liquid is 66°F using a closed cup Herzog tester. Flame extension is between 16-18 inches with no flashback. Fire Extinguishing Agents: All types. Special Fire Fighting Procedures: N/A Appearance and OdorFloral/Fruity odor Unusual Fire and Explosion Hazards: Alcohol flames may not be readily visible. Exposure to temperatures over 120°F (49°C) may cause bursting or venting. Keep containers cool. Use equipment or shielding to protect personnel from