The Clorox Company 1221 Broadway
Oakland, CA 94612

Material Safety Data Sheet

| Tel. (510) 271-7000 | | | Data Sneet | |
|---|---------------|---|--------------------------|--|
| 1 / | | ICED FLOOR CLEANE | R | |
| | RANCED LIQUID | | | |
| Other Designations | Distributor | | Emergency Telephone Nos. | |
| Clorox Sa 1221 E | | For Medical Emergencies call: (800) 446-1014 For Transportation Emergencies Chemtrec (800) 424-9300 III Hazardous Ingredients Ingredient Concentration Worker Exposure Limit Isopropyl alcohol 1 – 5% 400 ppm - TLV-TWA ^a 400 ppm - TLV-TWA ^a 400 ppm - TLV-STEL ^c Poly(hexamethylenebiguanide) hydrochloride 0.10% n/a CAS #32289-58-0 **TLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average bPEL = OSHA Permissible Exposure Limit - Time Weighted Average cTLV-STEL = ACGIH Threshold Limit Value - Short Term Exposure Limit None of the materials in this product are on the IARC, OSHA, or NTP carcinogen lists. V Transportation and Regulatory Data DOT: Not restricted per 49 CFR 173.120(a)(3) and Appendix H. IMO: Not restricted per IMDG Code Page 0016 Paragraph 5.1.3.1.1. IATA: Not restricted per IATA D.G.R. Sections 3.3.1.2 and 3.3.5. TSCA Status: All components of this product are on the TSCA inventory. EPA - SARA Title III/CERCLA: Packaged product is not reportable under Sections 311/312. This product contains no chemicals which are regulated under Section 313 and contains glycol ethers (<5%) which is regulated under Section 304/CERCLA. | | |
| VI Spill Procedures/Waste Disposal | | VII Reactivity Data | | |
| Spill Procedures: Absorb and containerize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material. Waste Disposal: Dispose of in accordance with all applicable federal, state, and local regulations. | | Stability: Stable Conditions to Avoid: Prolonged temperatures above 120 F This product is stable under normal use and storage conditions. | | |
| VIII Fire and Explosion Data | | IX Physical Data | | |
| Flash Point: >93°C (Herzog MC 315 automatic tester). Erdco/Sustained Combustion – Failed to sustain combustion Fire Extinguishing Agents: Dry chemical, carbon dioxide (CO ₂), foam or water spray. | | Specific gravity Viscosity Solubility in water | | |