The Clorox Company 1221 Broadway Oakland, CA 94612 Tel. (510) 271-7000

Material Safety Data Sheet

| Tel. (510) 271-7000 | | | | u 01100t |
|---|-----------------|--|---|----------|
| | PREMOISTENED | FLOOR WIPES | | |
| | D FLOOR CLEANII | NG WIPES | | |
| Other Designations | Distributor | | Emergency Telephone Nos. | |
| | 1221 B | es Company roadway CA 94612 | For Medical Emergencies call: (800) 446-1014 For Transportation Emergencies Chemtrec (800) 424-9300 | |
| II Health Hazard Data | | III Hazardous Ingredients | | |
| Eye contact may result in temporary conjunctival redness. No medical conditions are known to be aggravated by exposure to this product. FIRST AID: If you experience symptoms, contact a poison control center or a doctor for treatment advice or call (800)446-1014 directly. EYE CONTACT: Flush eyes with plenty of water for 15 minutes. If irritation persists, call a physician. IV Special Protection and Precautions The following recommendations are given for production facilities and for other conditions and situations where there is increased potential for accidental, large-scale or prolonged exposure. Hygienic Practices: Wash hands after direct contact. Engineering Controls: Use local exhaust to minimize exposure to product mist or vapors. Personal Protective Equipment: Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact. | | Ingredient Concentration Sopropyl alcohol 1 – 5% 400 ppm - TLV-TWA® 400 ppm - TLV-TWA® 400 ppm - TLV-STEL® 500 ppm - TLV-STEL® 700 ppm - T | | |
| VI Spill Procedures/Waste Disposal Spill Procedures: Absorb and containerize. Wash residual down to | | VII Reactivity Stability: Stable | Data | |
| sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material. | | Conditions to Avoid: Prolonged temperatures above 120° F | | |
| <u>Waste Disposal</u> : Dispose of in accordance with all applicable federal, state, and local regulations. | | This product is stable under normal use and storage conditions. | | |
| VIII Fire and Explosion Data | | IX Physical D | ata | |
| Flash Point: >93°C (Herzog MC 315 automatic tester). Erdco/Sustained Combustion – Failed to sustain combustion Fire Extinguishing Agents: Dry chemical, carbon dioxide (CO ₂), foam or water spray. | | pH | | |

©1963, 1991 THE CLOROX COMPANY