

Clorox Professional Products Company

1221 Broadway Oakland, CA 94612 Tel. (510) 271-7000

| I Product: COMMERCIA | L SOLUTIONS® UL | TRA CLOROX® GERM | ICIDAL BLEACH I |
|--|---|--|---|
| Description: CLEAR, LIGH | T YELLOW LIQUID | WITH CHLORINE ODC | 0R |
| Other Designations | Distributor | | Emergency Telephone Nos. |
| EPA Reg. No. 67619-8 Sodium Hypochlorite Solution | Clorox Sales Company 1221 Broadway Oakland, CA 94612 | | For Medical Emergencies, call 1-800-446-1014 For Transportation Emergencies, call Chemtrec 1-800-424-9300 |
| II Health Hazard Data | | III Hazardous | Ingredients |
| DANGER: CORROSIVE. May cause severe irritation or damage to eyes and skin. Harmful if Swallowed. The following medical conditions may be aggravated by exposure to high concentrations of vapor or mist; heart conditions or chronic respiratory problems such as asthma, chronic bronchitis, or obstructive lung disease. Some clinical reports suggest a low potential for sensitization upon exaggerated exposure to sodium hypochlorite, particularly on damaged or irritated skin. Routine clinical tests conducted on intact skin with Clorox Liquid Bleach found no sensitization in the test subjects. Under normal consumer use conditions the likelihood of any adverse health effects are low. | | | Concentration Worker Exposure Limit 6.0 - 7.35% Not established. < 0.2% |
| FIRST AID: | | None of the ingredients in this product are on the IARC, NTP or OSHA carcinogen list. | |
| EYE CONTACT: Rinse with plenty of water for at least 15 minutes. Get prompt medical attention. | | caronogen nat. | |
| SKIN CONTACT: Wash skin thoroughly with soap and wat | er. | | |
| <u>INGESTION</u> : Drink large amounts of water. DO NOT induce vomiting. Call a physician or poison control center immediately. | | | |
| INHALATION: If breathing problems develop, remove to free | sh air. | | |
| | | | |
| IV Special Protection and Precaution | IS | V Transportat | ion and Regulatory Data |
| IV Special Protection and Precaution Hygienic Practices: Wear safety glasses. With repeated wear nitrile, neoprene, or butyl rubber gloves. Wash after of Avoid breathing vapors. Engineering Controls: Use general ventilation to minimize emist. Work Practices: Avoid eye and skin contact and inhalation of the second secon | l or prolonged use, ontact with product. exposure to vapor or | DOT: Not restricted p I <u>MDG</u> : Not restricted p I <u>ATA</u> : Not restricted p <u>EPA - SARA Title III/C</u> This product is regulated u | er 49CFR172.101(c)(12)(iv). ber IMDG Code Page 0021 Paragraph 5.3.5. er IATA D.G.R. Special provision A3. |
| <u>Hygienic Practices</u> : Wear safety glasses. With repeated wear nitrile, neoprene, or butyl rubber gloves. Wash after of Avoid breathing vapors. <u>Engineering Controls</u> : Use general ventilation to minimize e mist. | l or prolonged use, ontact with product. exposure to vapor or | DOT: Not restricted p I <u>MDG</u> : Not restricted p I <u>ATA</u> : Not restricted p <u>EPA - SARA Title III/C</u> This product is regulated u sodium hydroxide whi | er 49CFR172.101(c)(12)(iv). ber IMDG Code Page 0021 Paragraph 5.3.5. er IATA D.G.R. Special provision A3. <u>ERCLA</u> : ted under Sections 311/312. This product contains no nder Section 313 and contains sodium hypochlorite and |
| <u>Hygienic Practices</u> : Wear safety glasses. With repeated wear nitrile, neoprene, or butyl rubber gloves. Wash after of Avoid breathing vapors. <u>Engineering Controls</u> : Use general ventilation to minimize e mist. <u>Work Practices</u> : Avoid eye and skin contact and inhalation of | l or prolonged use, ontact with product. exposure to vapor or | DOT: Not restricted p I <u>MDG</u> : Not restricted p I <u>ATA</u> : Not restricted p <u>EPA - SARA Title III/C</u> This product is regulated u sodium hydroxide whi | er 49CFR172.101(c)(12)(iv). ber IMDG Code Page 0021 Paragraph 5.3.5. er IATA D.G.R. Special provision A3. <u>ERCLA</u> : ted under Sections 311/312. This product contains no nder Section 313 and contains sodium hypochlorite and ch are regulated under Section 304/CERCLA. ponents of this product are on the TSCA Inventory. |
| Hygienic Practices: Wear safety glasses. With repeated wear nitrile, neoprene, or butyl rubber gloves. Wash after or Avoid breathing vapors. Engineering Controls: Use general ventilation to minimize emist. Work Practices: Avoid eye and skin contact and inhalation of KEEP OUT OF THE REACH OF CHILDREN. VI Spill Procedures: Absorb and containerize. Wash residu sewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple pr should evaluate the MSDS's of the products for incompa hypochlorite. Breathing protection should be worn in encl ventilated areas until hazard assessment is complete. Waste Disposal: Dispose of in accordance with all applied | I or prolonged use, ontact with product. exposure to vapor or of vapor or mist. al down to sanitary to assure ability to oducts, responders atibility with sodium osed, and/or poorly | DOT: Not restricted p I <u>MDG</u> : Not restricted p I <u>ATA</u> : Not restricted p <u>EPA - SARA Title III/C</u> This product is regulated u sodium hydroxide whit <u>TSCA Status</u> : All com VII Reactivity Stable under normal Reacts with other hor removers, vinegar, hazardous gases, suc | er 49CFR172.101(c)(12)(iv). ber IMDG Code Page 0021 Paragraph 5.3.5. er IATA D.G.R. Special provision A3. <u>ERCLA</u> : ted under Sections 311/312. This product contains no nder Section 313 and contains sodium hypochlorite and ch are regulated under Section 304/CERCLA. ponents of this product are on the TSCA Inventory. |
| Hygienic Practices: Wear safety glasses. With repeated wear nitrile, neoprene, or butyl rubber gloves. Wash after or Avoid breathing vapors. Engineering Controls: Use general ventilation to minimize emist. Work Practices: Avoid eye and skin contact and inhalation of KEEP OUT OF THE REACH OF CHILDREN. VI Spill Procedures: Absorb and containerize. Wash residu sewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple pr should evaluate the MSDS's of the products for incompa hypochlorite. Breathing protection should be worn in encl ventilated areas until hazard assessment is complete. Waste Disposal: Dispose of in accordance with all applic and local regulations. | I or prolonged use, ontact with product. exposure to vapor or of vapor or mist. al down to sanitary to assure ability to oducts, responders atibility with sodium osed, and/or poorly | DOT: Not restricted p I <u>MDG</u> : Not restricted p I <u>ATA</u> : Not restricted p <u>EPA - SARA Title III/C</u> This product is regulated u sodium hydroxide whi <u>TSCA Status</u> : All com VII Reactivity Stable under normal Reacts with other hor removers, vinegar, hazardous gases, suc contact with metal mag | er 49CFR172.101(c)(12)(iv). ber IMDG Code Page 0021 Paragraph 5.3.5. er IATA D.G.R. Special provision A3. <u>ERCLA</u> : ted under Sections 311/312. This product contains no nder Section 313 and contains sodium hypochlorite and ch are regulated under Section 304/CERCLA. ponents of this product are on the TSCA Inventory. Data use and storage conditions. Strong oxidizing agent. pusehold chemicals such as toilet bowl cleaners, rust acids or ammonia containing products to produce h as chlorine and other chlorinated species. Prolonged y cause pitting or discoloration. |
| Hygienic Practices: Wear safety glasses. With repeated wear nitrile, neoprene, or butyl rubber gloves. Wash after or Avoid breathing vapors. Engineering Controls: Use general ventilation to minimize emist. Work Practices: Avoid eye and skin contact and inhalation of KEEP OUT OF THE REACH OF CHILDREN. VI Spill Procedures: Absorb and containerize. Wash residu sewer. Contact the sanitary treatment facility in advance process washed-down material. For spills of multiple pr should evaluate the MSDS's of the products for incompa hypochlorite. Breathing protection should be worn in encl ventilated areas until hazard assessment is complete. Waste Disposal: Dispose of in accordance with all applied | I or prolonged use, ontact with product. exposure to vapor or of vapor or mist. al down to sanitary to assure ability to oducts, responders atibility with sodium osed, and/or poorly | DOT: Not restricted p I <u>MDG</u> : Not restricted p I <u>ATA</u> : Not restricted p <u>EPA - SARA Title III/C</u> This product is regulated u sodium hydroxide whit <u>TSCA Status</u> : All com VII Reactivity Stable under normal Reacts with other hor removers, vinegar, hazardous gases, suc | er 49CFR172.101(c)(12)(iv). ber IMDG Code Page 0021 Paragraph 5.3.5. er IATA D.G.R. Special provision A3. <u>ERCLA</u> : ted under Sections 311/312. This product contains no nder Section 313 and contains sodium hypochlorite and ch are regulated under Section 304/CERCLA. ponents of this product are on the TSCA Inventory. Data use and storage conditions. Strong oxidizing agent. pusehold chemicals such as toilet bowl cleaners, rust acids or ammonia containing products to produce h as chlorine and other chlorinated species. Prolonged y cause pitting or discoloration. |

©1963, 1991 THE CLOROX COMPANY