The Clorox Company 1221 Broadway Oakland, CA 94612 Tel. (510) 271-7000

Material Safety Data Sheet

Tel. (510) 271			ata Onoot	
		OORIZING WET FLOO	R WIPES	
Description: PREMOISTENE	D FLOOR CLEANII	NG WIPES		
Other Designations	Distributor		Emergency	/ Telephone Nos.
	1221 B	es Company roadway CA 94612	For Medica (80) For Transportatio	al Emergencies call: 0) 446-1014 n Emergencies Chemtrac 0) 424-9300
II Health Hazard Data		III Hazardous Ingredients		
Eye contact may result in temporary conjunctival redness. No medical conditions are known to be aggravated by exposure to this product. FIRST AID: If you experience symptoms, contact a poison control center or a doctor for treatment advice or call (800)446-1014 directly. EYE CONTACT: Flush eyes with plenty of water for 15 minutes. If irritation persists, call a physician. IV Special Protection and Precautions The following recommendations are given for production facilities and for other conditions and situations where there is increased potential for accidental, large-scale or prolonged exposure. Hygienic Practices: Wash hands after direct contact. Engineering Controls: Use local exhaust to minimize exposure to product mist or vapors. Personal Protective Equipment: Wear safety glasses. Wear rubber or neoprene gloves if there is the potential for repeated or prolonged skin contact.		Ingredient Concentration Isopropyl alcohol 1 – 5% 400 ppm - TLV-TWA® 400 ppm - TLV-TWA® 400 ppm - PEL® 500 ppm - TLV-STEL® 500		
VI Spill Procedures/Waste Disposal Spill Procedures: Absorb and containerize. Wash residual down to sanitary sewer. Contact the sanitary treatment facility in advance to assure ability to process washed-down material. Waste Disposal: Dispose of in accordance with all applicable federal, state, and local regulations.		VII Reactivity Data Stability: Stable Conditions to Avoid: Prolonged temperatures above 120° F This product is stable under normal use and storage conditions.		
VIII Fire and Explosion Data		IX Physical D		
Flash Point: >93°C (Herzog MC 315 automatic tester). Erdco/Sustained Combustion – Failed to sustain combustion Fire Extinguishing Agents: Dry chemical, carbon dioxide (CO ₂), foam or water spray.		pH		

©1963, 1991 THE CLOROX COMPANY