


JON-WOOD POLYURETHANE WOOD FLOOR FINISH

National Fire Protection Association (NFPA)	Fire Hazard	Hazardous Material Information System (HMIS)	Health	2
	Health		2	
	Reactivity		Reactivity	0
Specific Hazard				
Protective Clothing		Emergency	Amber. Liquid. See Section 9.	
		Overview	CAUTION: COMBUSTIBLE. May cause eye and skin irritation.	

Section 1. Chemical Product and Company Identification				
Product Name	JON-WOOD POLYURETHANE WOOD FLOOR FINISH		Code	14675
Product Use	Industrial/Institutional: Floor care.		PMS#	453443
MSDS#	115653001		Validation Date	2/2/2005
U.S. Headquarters	Canadian Headquarters		Print Date	2/2/2005
JohnsonDiversey, Inc. 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.johnsondiversevy.com	JohnsonDiversey - Canada, Inc. 2401 Bristol Circle Oakville, Ontario L6H 6P1 Phone: 1-800-668-3131		Supersedes	1/30/2002
			In Case of Emergency	(800) 851-7145

Section 2. Composition and Information on Ingredients				
Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Polyurethane Mineral Spirits	8052-41-3	1-5 10-30	Not available. OSHA (United States). TWA: 525 mg/m ³ ACGIH (United States). TWA: 525 mg/m ³	Not available. ORAL (LD50): Acute: >5000 mg/kg [Rat]. DERMAL (LD50): Acute: >3000 mg/kg [Rabbit].
Petroleum distillates	64742-47-8	30-60	Not available.	Not available.

Section 3. Hazards Identification	
Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health Effects	<p><i>Eyes</i> May be moderately irritating to eyes.</p> <p><i>Skin</i> May be moderately irritating to skin.</p> <p><i>Inhalation</i> May be irritating to nose, throat, and respiratory tract.</p> <p><i>Ingestion</i> May be irritating to mouth, throat and stomach.</p>
Medical Conditions Aggravated by Overexposure:	Persons with pre-existing skin disorders may be more susceptible to irritating effects.
See Toxicological Information (section 11)	

Section 4. First Aid Measures

Eye Contact	Flush immediately with plenty of water. If irritation persists, get medical attention.
Skin Contact	Flush immediately with plenty of water. If irritation persists, get medical attention.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention.
Ingestion	Immediately drink one cupful of water or milk. Never give anything by mouth to an unconscious person. Get medical attention.

Section 5. Fire Fighting Measures

Flammability of the Product	COMBUSTIBLE.
Flash Points	Closed cup: 43.333°C (110°F).
Products of Combustion	None known.
Fire Fighting Media and Instructions	Vapors are heavier than air and may spread along floors. Avoid all possible sources of ignition (spark or flame). Use water spray to keep fire exposed containers cool. dry chemical, carbon dioxide.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8).
Special Remarks on Fire and Explosion Hazards	Material may burn in heat of fire. Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).
Environmental Precautions and Clean-up Methods	Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin and clothing. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Use only in well-ventilated areas. FOR COMMERCIAL AND INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	No special ventilation requirements. General room ventilation is adequate.
Personal Protection	
<i>Eyes</i>	Safety glasses with side shields.
<i>Hands</i>	No special requirements under normal use conditions. For prolonged or repeated contact with skin: Neoprene gloves. Rubber gloves.
<i>Respiratory</i>	No special requirements under normal use conditions.
<i>Feet</i>	No special requirements under normal use conditions.
<i>Body</i>	If major exposure is possible, wear suitable protective clothing.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Hydrocarbon solvent (Slight.)
Color	Amber.
pH	Not applicable
Specific Gravity	0.89
Solubility in water	Negligible.

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Conditions of Instability	None known.
Incompatibility with Various Substances	Reactive with oxidizing agents, acids.
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.
Hazardous Polymerization	Will not occur.

Section 11. Toxicological Information

Acute toxicity	ORAL (LD50) Estimated to be greater than 5000 mg/kg (rat).
Effects of Chronic Exposure	None known.
Other Toxic Effects	None known.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information	Undiluted product is regulated under environmental and transportation laws as an ignitable waste. Dispose of according to all federal, state and local applicable regulations.
--------------------------	--

Section 14. Transport Information

DOT Classification	
DOT Proper Shipping Name	Please refer to the Bill of Lading/receiving documents for up to date shipping information.
TDG Classification	
TDG Proper Shipping Name	Please refer to the Bill of Lading/receiving documents for up to date shipping information.

Section 15. Regulatory Information

Reporting in this section is based on ingredients disclosed in Section 2

US Regulations

Federal SARA 302/304/311/312 hazardous chemicals: mineral spirits
SARA 311/312 MSDS distribution - chemical inventory - hazard identification: mineral spirits

State New Jersey: mineral spirits
Massachusetts RTK: mineral spirits
Pennsylvania RTK: mineral spirits

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information Not applicable.

Canadian Regulations

WHMIS Classification CLASS B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
CLASS D-2B: Material causing other toxic effects (TOXIC).

**JON-WOOD POLYURETHANE WOOD FLOOR
FINISH**

WHMIS Icon



Registered Product Information Not applicable.

Chemical Inventory Status All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory. All the ingredients are on the DSL list.

Section 16. Other Information

Other Special Considerations Not available.

Version 2.01

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.