

Material Safety Data Sheet

SPITFIRE NB SC

National Fire Protection Association (NH	Fire Hat FPA) Health 3 Specific H	1 Reactivity	Hazardous I Information (HMIS)		Health3Fire Hazard0Reactivity0
Protective Clothing	<u> </u>	Emergency Overview			USES EYE AND SKIN BURNS.
Section 1. Chemical Product and Company Identification					
Product Name	SPITFIRE NB SC			Code	4993 & 4994
Product Use	Industrial/Institutional: Clean to be diluted prior to use.	ning product. This product	ct is intended	PMS#	438094
MSDS#	113707002			Validation Dat	e 1/06/2005
U.S. Headquarters		Canadian Headquarters		Print Date	1/06/2005
Johnson Wax Professional 8310 16th Street		Johnson Wax Professio 100 Matheson Blvd. East Mississerupe, Optoria L	st, Suite 203	Supersedes	11/7/2001
Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com		Mississauga, Ontario L4 Phone: (905) 755-0913 (888) 746-5971		<u>In Case of</u> <u>Emergency</u>	(800) 851-7145

Section 2. Composition and Information on Ingredients				
Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Sodium Xylene Sulfonate Potassium Hydroxide	1300-72-7 1310-58-3	1-5 1-5	Not available. CEIL: 2 (mg/m ³) from OSHA (PEL) [United States] STEL: 2 (mg/m ³) from ACGIH (TLV) [United States]	Not available. ORAL (LD50): Acute: 365 mg/kg [Rat]. 273 mg/kg [Male. Rat].
Dipropylene Glycol Methyl Ether	34590-94-8	3-7	TWA: 600 STEL: 900 (mg/m ³) from OSHA (PEL) [United States] SKIN TWA: 606 STEL: 909 (mg/m ³) from ACGIH (TLV) [United States] SKIN	ORAL (LD50): Acute: 5119 mg/kg [Rat]. DERMAL (LD50): Acute: 9480 mg/kg [Rabbit].
Tripotassium Salt of EDTA Monoethanolamine	17572-97-3 141-43-5	3-7 5-10	Not available. TWA: 8 STEL: 15 (mg/m ³) from OSHA (PEL) [United States] TWA: 7.5 STEL: 15 (mg/m ³) from ACGIH (TLV) [United States]	Not available. ORAL (LD50): Acute: 1720 mg/kg [Rat]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit].
Propylene Glycol N-Propyl Ether Water	1569-01-3 7732-18-5	10-30 40-70	Not available. Not available.	Not available. Not available.

Section 3. Hazards Identification

Routes of Entry	Inhalation. Skin contact. Eye contact.
Potential Acute Health Effects	
Eyes	Corrosive. May cause permanent damage including blindness.
Skin	Corrosive. May cause permanent damage.
Inhalation	May cause irritation and corrosive effects to nose, throat and respiratory tract.
Ingestion	Corrosive. May cause burns to mouth, throat, and stomach.
Medical Conditions Aggravated by Overexposure:	Individuals with chronic respiratory disorders such as asthma, chronic bronchitis, emphysema, etc., may be more susceptible to irritating effects.
See Toxicological Information	(section 11)

Continued on Next Page

Section 4. First Aid Measures

Johnson wax PROFESSIONAL

Eye Contact	Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention immediately.
Skin Contact	Flush immediately with plenty of water for at least 15 minutes. Get medical attention immediately.
Inhalation	If breathing is difficult: Remove to fresh air. Get medical attention immediately.
Ingestion	Do not induce vomiting! Immediately drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention immediately.

Section 5. Fire Fighting Measures

Flammability of the Product Flash Points	None known. CLOSED CUP: >93.3°C (199.9°F).
Products of Combustion	None known.
Fire Fighting Media and Instructions	Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used.
Special Remarks on Fire and Explosion Hazards	None known.

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).
Environmental Precautions and Clean-up Methods	In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up.

Section 7. Handling and Storage

Handling	Avoid contact with eyes, skin, and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR INDUSTRIAL USE ONLY.
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Good general ventilation should be sufficient to control airborne levels. Respiratory protection is not required if good ventilation is maintained.
Personal Protection	
Eyes	Chemical splash goggles.
Hands	Chemical resistant gloves.
Respiratory	If mists/vapors are not adequately controlled by ventilation, use appropriate respiratory protection to avoid over exposure. A respiratory protection program that meets OSHA's 29 CFR 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.
Feet	Protective footwear.
Body	If major exposure is possible, wear suitable protective clothing and footwear.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid.
Odor	Characteristic.
Color	Dark Red.
рН	13.5 [Basic.]
Specific Gravity	1.04
Solubility in water	Complete.

Johnson wax PROFESSIONAL

SPITFIRE NB SC

Section 10. Stability and Reactivity

,	•
Stability and Reactivity	The product is stable.
Conditions of Instability	None known.
Incompatibility with Various Substances	Reactive with acids.
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.
Hazardous Polymerization	Will not occur.

Section 11. Toxicological Information

Acute toxicityCorrosive.Effects of Chronic ExposureNone known.Other Toxic EffectsNot available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information

Undiluted product is regulated under environmental and transportation laws as a corrosive waste. Dispose of according to all federal, state and local regulations.

Section 14. Transport Information

DOT Classification

DOT Classification	
DOT Proper Shipping Name	Please refer to the Bill of Lading/receiving documents for up to date shipping information.
TDG Classification	
TDG Proper Shipping Name TDG Class	Please refer to the Bill of Lading/receiving documents for up to date shipping information.

Section 15. Regulatory Information

Reporting in this section i	is based on ingredients disclosed in Section 2
US Regulations	
Federal	Clean Water Act (CWA) 311: Potassium Hydroxide CERCLA: Hazardous substances.: Potassium Hydroxide
State	New Jersey spill list: Potassium Hydroxide New Jersey: Monoethanolamine, Potassium Hydroxide Massachusetts spill list: Monoethanolamine, Potassium Hydroxide Massachusetts RTK: Monoethanolamine, Potassium Hydroxide Pennsylvania RTK: Monoethanolamine, Potassium Hydroxide, Propylene Glycol
	This product is not subject to the reporting requirements under California's Proposition 65.
Registered Product Information	Not applicable.
Canadian Regulations	
WHMIS Classification	CLASS E: Corrosive liquid.
WHMIS Icon	
Registered Product Information	Not applicable.



SPITFIRE NB SC

Chemical Inventory Status

All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Section 16. 0	Other Information
Other Special Considerations	Not available.
Version	1.01
Notice to Reader	

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.