

SPITFIRE SC POWER CLEANER

| National Fire Protection Association (N | | re Hazard Reactivity | Hazardous Informatio (HMIS) | n System | Health2Fire Hazard0Reactivity0 | |
|--|--|---|--|---------------------------------------|---------------------------------|-----|
| Protective | Spo | ecific Hazard Emergency | Red. Liquid. S | Son Soction 0 | | |
| Clothing | | Overview | | | WALLOWED. CAUSES E | YE |
| Section 1. C | hemical Product an | d Company Identificatio | on | | | |
| Product Name | SPITFIRE SC PO | VER CLEANER | | Code | 3723 & 4966 & 306356 3165361 | 8 & |
| Product Use | Industrial/Institutional: to be diluted prior to us | Cleaning product. This produ se. | ct is intended | PMS# | 3104956 | |
| MSDS# | 113703002 | | | Validation Date | 7/29/2003 | |
| U.S. Headquarters | | Canadian Headquarter | s | Print Date | 7/29/2003 | |
| Johnson Wax Professional 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249 MSDS Internet Address: www.jwp.com | | | Johnson Wax Professional 100 Matheson Blvd. East, Suite 203 | | 7/22/2003. | |
| | | Mississauga, Ontario L Phone: (905) 755-0913 (888) 746-5971 | 4Z 2G7 | <u>In Case of</u> <u>Emergency</u> | (800) 851-7145 | |

| Ingredients | CAS # | % by Weight | Exposure Limits | LC50/LD50 |
|---------------------------------|------------|-------------|---|--|
| | | | | |
| Potassium Hydroxide | 1310-58-3 | 1-5 | OSHA (United States). CEIL: 2 mg/m ³ ACGIH (United States). STEL: 2 mg/m ³ | ORAL (LD50): Acute: 365 mg/kg [Rat]. 273 mg/kg [Male. Rat]. |
| Ethylenediaminetetraacetic Acid | 60-00-4 | 1-5 | Not available. | Not available. |
| Ethoxylated Alcohol | 68551-12-2 | 1-5 | Not available. | Not available. |
| Monoethanolamine | 141-43-5 | 5-10 | OSHA (United States). TWA: 8 mg/m ³ STEL: 15 mg/m ³ ACGIH (United States). TWA: 7.5 mg/m ³ STEL: 15 mg/m ³ | ORAL (LD50): Acute: 1720 mg/kg [Rat]. DERMAL (LD50): Acute: 1018 mg/kg [Rabbit]. |
| Propylene Glycol | 57-55-6 | 10-30 | Not available. | ORAL (LD50): Acute: 20000 mg/kg [Rat]. DERMAL (LD50): Acute: 20800 mg/kg [Rabbit]. |
| 2-Butoxyethanol | 111-76-2 | 25-35 | OSHA (United States). TWA: 120 mg/m ³ ACGIH (United States). TWA: 97 mg/m ³ | ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hour(s) [Rat]. |
| Water | 7732-18-5 | 30-60 | Not available. | Not available. |

Section 3. Hazards Identification

Routes of Entry Eye contact. Skin contact Inhalation.

Potential Acute Health Effects

Eyes May be severely irritating to eyes.

Skin May be mildly irritating to skin.

Inhalation May be irritating to nose, throat, and respiratory tract.

Ingestion Harmful if swallowed. May cause kidney and central nervous system effects. Effects include: headache, nausea and dizziness. May cause abdominal discomfort, nausea, vomiting and diarrhea.



Medical Conditions Persons with pre-existing skin disorders may be more susceptable to irritating effects. Aggravated by Overexposure:

See Toxicological Information (section 11)

| Section 4. First Aid Measures | |
|-------------------------------|--|
| Eye Contact | Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Get medical attention. |
| Skin Contact | Flush immediately with plenty of water for at least 15 minutes. Get medical attention. |
| Inhalation | If breathing is difficult: Remove to fresh air. Get medical attention. |
| Ingestion | Immediately drink one cupful of water or milk. Call medical attendant, medical doctor, or poison control center immediately. |

Section 5. Fire Fighting Measures

| Flammability of the Product | None known. |
|---|---|
| Flash Points | Closed cup: >93.333°C (200°F). |
| Products of Combustion | None known. |
| Fire Fighting Media and Instructions | Extinguish with water spray or carbon dioxide, dry chemical powder or appropriate foam. Normal fire fighting procedure may be used. |
| Protective Clothing (Fire) | Put on appropriate personal protective equipment (see Section 8). |
| Special Remarks on Fire and Explosion Hazards | None known. |

Section 6. Accidental Release Measures

| Personal Precautions | Put on appropriate personal protective equipment (see Section 8). |
|---|--|
| Environmental Precautions and Clean-up Methods | In the event of major spillage: Use appropriate containment to avoid environmental contamination. Sweep or scrape up material. Place in suitable clean, dry containers for disposal by approved methods. Use a water rinse for final clean-up. |

Section 7. Handling and Storage

| Handling | Avoid contact with eyes, skin and clothing. Do not taste or swallow. Avoid breathing vapors or spray mists. Wash thoroughly after handling. Remove and wash contaminated clothing and footwear before re-use. Product residue may remain on/in empty containers. All precautions for handling the product must be used in handling the empty container and residue. FOR COMMERCIAL AND INDUSTRIAL USE ONLY. |
|----------|---|
| Storage | Protect from freezing. Store in a dry, cool and well-ventilated area. KEEP OUT OF REACH OF CHILDREN. |

Section 8. Exposure Controls/Personal Protection

Engineering Controls No special ventilation requirements. General room ventilation is adequate.

Personal Protection

Eyes Safety glasses with side shields.

Hands For prolonged or repeated contact with skin: Chemical resistant gloves.

Respiratory No special requirements under normal use conditions.

Feet No special requirements under normal use conditions.

Body If major exposure is possible, wear suitable protective clothing.

Section 9. Physical and Chemical Properties

| Physical State and | Liquid. |
|-----------------------------------|----------------|
| Appearance | |
| Odor | Fresh. |
| Color | Red. (Dark.) |
| pH | >13 [Basic.] |
| Specific Gravity | 1.02 |
| Boiling/Condensation Point | 74°C (165.2°F) |

Continued on Next Page



SPITFIRE SC POWER CLEANER

Melting/Freezing Point Solubility in water <-1°C (30.2°F) Complete.

| Section 10. Stability and Reactivity | | |
|--|---|--|
| Stability and Reactivity | The product is stable. | |
| Conditions of Instability | None known. | |
| Incompatibility with Various Substances | Reactive with acids. | |
| Hazardous Decomposition Products | When exposed to fire: Produces normal products of combustion. | |
| Hazardous Polymerization | Will not occur. | |
| | | |

Section 11. Toxicological Information

| Acute toxicity | Acute oral toxicity (LD50) Estimated to be greater than 2000 mg/kg (rat) |
|-----------------------------|--|
| Effects of Chronic Exposure | None known. |
| Other Toxic Effects | None known. |
| | |

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information

No special precautions. Dispose of according to all federal, state and local applicable regulations.

Section 14. Transport Information

| • | |
|-----------------------------|---|
| DOT Classification | |
| DOT Proper Shipping Name | Please refer to the Bill of Lading/receiving documents for up to date shipping information. |
| TDG Classification | |
| TDG Proper Shipping Name | Please refer to the Bill of Lading/receiving documents for up to date shipping information. |

TDG Class

Section 15. Regulatory Information

| Reporting in this section i | is based on ingredients disclosed in Section 2 |
|-----------------------------------|--|
| US Regulations | |
| | Clean Water Act (CWA) 311: Potassium hydroxide, Ethylenediaminetetraacetic Acid CERCLA: Hazardous substances.: Potassium hydroxide, Ethylenediaminetetraacetic Acid, 2-Butoxyethanol |
| | New Jersey spill list: Potassium hydroxide, Ethylenediaminetetraacetic Acid, 2-Butoxyethanol New Jersey: Monoethanolamine, Potassium hydroxide, Ethylenediaminetetraacetic Acid, 2-Butoxyethanol Massachusetts spill list: Monoethanolamine, Potassium hydroxide, Ethylenediaminetetraacetic Acid, 2-Butoxyethanol Massachusetts RTK: Monoethanolamine, Potassium hydroxide, Ethylenediaminetetraacetic Acid, 2-Butoxyethanol Pennsylvania RTK: Propylene Glycol, Monoethanolamine, Potassium hydroxide, Ethylenediaminetetraacetic Acid, 2-Butoxyethanol |
| | This product is not subject to the reporting requirements under California's Proposition 65. |
| Registered Product Information | Not applicable. |
| Canadian Regulations | |

Canadian NPRI Canadian NPRI: 2-Butoxyethanol.



SPITFIRE SC POWER CLEANER

WHMIS Classification Class D-2B: Material causing other toxic effects (TOXIC).

| WHMIS Icon | |
|----------------------------------|--|
| Registered Produc Information | |
| Chemical Inventory Status | All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory |

| Section 16. Other Information | | |
|---------------------------------|----------------|---|
| Other Special Considerations | Not available. | |
| Version | 2.01 | |
| | | n sources considered technically reliable. It does not constitute a warranty, express or implied, |

as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.