



## MATERIAL SAFETY DATA SHEET

CURE-O-THANE Oil  
Modified Urethane  
Sanding Seal

MSDS Ref. No: f-00334001  
Date Prepared: 05/13/2003  
Date Revised: 05/13/2003

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME/USE:** CURE-O-THANE Oil Modified Urethane Sanding Seal

**MSDS CODE:** 3044244

**PRODUCT CODE:** 7022050

#### MANUFACTURER

Magee  
67 Forest Street  
Marlborough, MA 01752

**Telephone Number:** 1-800-786-2433  
**Emergency Telephone (24 hours):** 1-800-228-5635  
**CHEMTREC (U.S./Can.):** 800-424-9300  
**CHEMTREC (Int'l):** +1 703-527-3887

### 2. COMPOSITION / INFORMATION ON INGREDIENTS

<u>INGREDIENT(S)</u>	<u>CAS#</u>	<u>% BY WEIGHT</u>
Oil modified urethane resin	NA	25 - 40
Mineral spirits	64742-47-8	40 - 60
Exempt mineral spirits	8052-41-3	10 - 25

See Section 8 for Exposure Limits NA - Not Applicable

**OSHA REGULATORY STATUS:** This product is classified as hazardous under OSHA regulations.

**WHMIS CLASS:** Class B- Division 3; Class D- Division 2B

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Clear, Amber Liquid . Solvent Odor. Harmful or Fatal if Swallowed. Harmful if Inhaled. May Cause Eye and Skin Irritation. Combustible.

#### POTENTIAL HEALTH EFFECTS (See Section 11 for Toxicological Information)

PRIMARY ROUTE(S) OF EXPOSURE:  Eye       Skin Contact       Skin Absorption  
 Inhalation       Ingestion

#### EFFECTS OF ACUTE EXPOSURE

**EYES:** May cause eye irritation. Symptoms may include redness and pain.

**SKIN:** May cause skin irritation. Symptoms may include redness, rash and mild swelling.

**INHALATION:** Harmful if inhaled. Symptoms may include coughing, chest discomfort, difficulty breathing and shortness of breath. High concentrations of vapor or mist may cause nose, throat and respiratory tract irritation. Symptoms may include coughing, wheezing and

shortness of breath. High concentrations of vapor or mist may also cause central nervous system effects including headache, dizziness and nausea.

**INGESTION:** Harmful or fatal if swallowed.

Ingestion may lead to aspiration into the lungs causing lung injury. May cause mouth, throat and stomach irritation. Symptoms may include nausea, vomiting and diarrhea. May also cause central nervous system effects including headache, dizziness and weakness.

**EFFECTS OF CHRONIC EXPOSURE:** Prolonged or repeated contact can cause defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

**MEDICAL CONDITIONS AGGRAVATED:** May aggravate pre-existing eye, skin and respiratory conditions.

## 4. FIRST AID MEASURES

**EYES:** Flush eyes with plenty of water while holding eyelids apart. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Do not put any medication in the victim's eyes unless instructed by a physician. Get medical attention.

**SKIN:** Flush thoroughly with plenty of water, then wash with soap and water. Remove saturated clothing. Get medical attention if irritation develops or persists. Thoroughly wash (or discard) clothing and shoes before reuse.

**INHALATION:** Remove to fresh air. If not breathing, give respiration; if breathing is difficult, give oxygen (by trained personnel only). Get immediate medical attention.

**INGESTION:** Do not induce vomiting. Immediately call poison control center, physician, or emergency number listed above.

## 5. FIRE FIGHTING MEASURES

**FLASH POINT AND METHOD:** 40°C (105°F)TCC

**FLAMMABLE LIMITS:** Not applicable.

**AUTOIGNITION TEMPERATURE:** Not applicable.

**EXTINGUISHING MEDIA:** Use water fog, dry chemical, CO<sub>2</sub>, or foam.

**HAZARDOUS COMBUSTION PRODUCTS:** Normal products of combustion (carbon monoxide and carbon dioxide).

**FIRE AND EXPLOSION HAZARDS:** Class II combustible liquid. This product is combustible and may be ignited by heat, sparks, flame, and other ignition sources. Vapors can travel to a source of ignition and flash back.

**FIRE FIGHTING INSTRUCTIONS:** Evacuate area. Cool containers exposed to fire with water. MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear should be worn.

## 6. ACCIDENTAL RELEASE MEASURES

See Section 8, Exposure Controls/Personal Protection and Section 3, Hazard Identification. Floors may be slippery. Use care to avoid falling. Ventilate spill area. Contain and isolate spill. Keep non-essential personnel from entering spill area. Use mop and absorbent to collect material for proper disposal. Rinse area with water.

## 7. HANDLING AND STORAGE

**HANDLING:** Follow label use directions. Do not mix with other chemicals unless instructed by label directions. Loosen closure cautiously before opening. Avoid contact with skin, eyes and clothing. Use with adequate ventilation. Avoid breathing vapor or mist. Use spark-proof tools. Wash thoroughly after handling. Remove contaminated clothing. Wash clothing and equipment before reuse. If strong odor is noticed or you experience slight dizziness, headache, nausea, or eye-watering - STOP - ventilation is not adequate. Leave area immediately. Empty containers retain residue and may be hazardous (See Section 14, Transport Information).

**STORAGE:** Keep container closed when not in use. Store away from incompatible materials. (See Section 10, Stability and Reactivity). Store away from direct sunlight. Keep away from heat, sparks and flame.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

---

**PERSONAL PROTECTIVE EQUIPMENT (PPE)**

**EYE:** Where eye contact is possible, wear safety glasses with side shields or chemical splash goggles (ANSI Z87.1 approved).

**SKIN:** Where skin contact is possible, chemical-resistant clothing (e.g., gloves) should be worn.

**RESPIRATORY:** No respiratory protection is required if ventilation is adequate and airborne concentrations are kept below exposure limits. When exposure limits may be exceeded, use appropriate respiratory protection (NIOSH)/MSHA-approved) to prevent overexposure.

**ENGINEERING CONTROLS:** Use only with adequate ventilation. Open all windows and doors. Use only with a cross ventilation of moving fresh air across the work area. Respiratory protection is not required if good ventilation is maintained.

**EXPOSURE LIMITS:**

<u>INGREDIENT(S)</u>	<u>OSHA PEL/STEL</u>	<u>ACGIH TLV/STEL</u>
Oil modified urethane resin	NE	NE
Mineral spirits	100 ppm 400 mg/m3 (Naphtha)	NA
Exempt mineral spirits	500 ppm 2900 mg/m3	100 ppm 525 mg/m3

NA - Not Available

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE:** Liquid

**ODOR:** Solvent

**APPEARANCE:** Clear, Amber

**pH:** Not Available

**PERCENT VOLATILE BY WEIGHT:** 70

**VAPOR PRESSURE:** Not Available

**VAPOR DENSITY:** Not Available

**BOILING POINT:** Not Available

**FREEZING/MELTING POINT:** Not Available

**SOLUBILITY IN WATER:** Insoluble

**EVAPORATION RATE:** Not Available

**SPECIFIC GRAVITY:** 0.85

**VISCOSITY:** Not Determined

**(VOC):** 593 g/l

**OCTANOL/WATER PARTITION COEFFICIENT:** Not Available

**ODOR THRESHOLD:** Not Available

**10. STABILITY AND REACTIVITY**

**STABILITY (CONDITIONS TO AVOID):** Stable.

**POLYMERIZATION:** Will not occur.

**HAZARDOUS DECOMPOSITION:** None known.

**INCOMPATIBLE MATERIALS:** Oxidizers (e.g., bleach).

**11. TOXICOLOGICAL INFORMATION**

**ACUTE DATA:** No data is available for this product. The following data are available for product ingredients:

<u>PRODUCT/INGREDIENT</u>	<u>ORAL LD<sub>50</sub> (rat)</u>	<u>DERMAL LD<sub>50</sub> (rabbit)</u>	<u>INHALATION LC<sub>50</sub> (rat)</u>
Oil modified urethane resin	Not Available	Not Available	Not Available
Mineral spirits	Not Available	Not Available	Not Available
Exempt mineral spirits	5000 - mg/kg	>3000 - Not Available	5500 - mg/m3 (4-hr)

**SENSITIZATION DATA:** No data available.

**CHRONIC DATA:**

Prolonged overexposure to aliphatic petroleum distillates by ingestion and inhalation has caused central nervous system effects in humans and laboratory animals; overexposure by inhalation has also caused kidney effects in animals.

**REPRODUCTIVE/TERATOGENIC DATA:** No data available.

**CARCINOGENIC/MUTAGENIC DATA:** Not listed as carcinogenic by NTP, IARC, or ACGIH or regulated as a carcinogen by OSHA.

**SYNERGISTIC MATERIALS:** No data available.

**12. ECOLOGICAL INFORMATION**

No data available.

**13. DISPOSAL CONSIDERATIONS**

Disposal of this material should be in accordance with local, state or provincial and federal regulations. The unused product, as manufactured, is a RCRA hazardous waste (Ignitable-D001) in accordance with 40 CFR 261. The product has not been evaluated by the Toxicity Characteristic Leachate Procedure (TCLP). According to RCRA, it is the responsibility of the waste generator to ensure proper disposal.

Rags or other waste, soaked with this product may spontaneously catch fire if improperly discarded. Immediately after use, place rags or waste in a sealed, water-filled metal container. Dispose of in accordance with local fire and waste regulations.

**14. TRANSPORT INFORMATION**

**DOT/TDG HAZARDOUS MATERIAL DESCRIPTION:** Not regulated

**15. REGULATORY INFORMATION**

*Not meant to be all-inclusive---selected regulations represented.*

**UNITED STATES**

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HAZARD CATEGORIES:** Under 40 CFR 370.2, this product meets the following hazard categories: Immediate, Delayed.

**313 REPORTABLE INGREDIENTS:** Xylene is subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

**CERCLA REGULATORY:** Not reportable under CERCLA.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA STATUS:** This product complies with all TSCA inventory requirements.

**MASSACHUSETTS, NEW JERSEY, PENNSYLVANIA RIGHT-TO-KNOW:**

**INGREDIENT(S)**

Oil modified urethane resin

Mineral spirits

Exempt mineral spirits

*NA - Not Applicable*

**CAS NO.    STATE LISTING**

NA    Not Listed

64742-47-8    Not Listed

8052-41-3    MA, NJ, PA

**CANADA**


**WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM):** Class B-Division 3, combustible liquid; Class D-Division 2B, eye and skin irritant. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**16. OTHER INFORMATION**

**HMIS RATING**

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>2</b>
<b>REACTIVITY</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>-</b>

**NFPA CODES:**



**APPROVED BY:** Product Safety & Regulatory

**MSDS STATUS**

**Revision No:** New MSDS

New MSDS

**APPROVAL DATE:** 05/13/2003

*The information on this data sheet represents our current data and best opinion as to the proper use in handling of the product under normal foreseeable conditions. Any use of this product which is not in conformance with this data sheet or product label, or which involves using the product in combination with any other product or any other process is the responsibility of the user.*