

RM-5138

RUBBERMAID COMMERCIAL PRODUCTS

MATERIAL SAFETY DATA SHEET

SECTION I

PRODUCT NAME OR NUMBER (as it appears on label): SeBreeze® Spring Garden Fragrance Aerosol Canister-8138		EMERGENCY TELEPHONE NO.: Safety Mgr. (640) 642-8288
MANUFACTURER'S NAME: Rubbermaid Commercial Products Inc.		DATE OF LAST REVISION: 01/04/89
ADDRESS (Number, Street, City, State and Zip Code): 3124 Valley Avenue, Winchester, VA 22601		MANUFACTURER'S D-U-N-S NO.: NA
HAZARDOUS MATERIAL DESCRIPTION (49 CFR 172.101) Consumer Commodity, ORM-D		
ADDITIONAL HAZARD CLASSES (as applicable): NFPA Rating System: Fire-3/Health-1/Reactivity-0		
CHEMICAL FAMILY: Aerosol Mixture	FORMULA: NA	

SECTION II - INGREDIENTS

(list all ingredients) 100% Needed

CAS REGISTRY NO.	%V	CHEMICAL NAME(S)	Listed as a Carcinogen in NTP, IARC or OSHA 1910(z) (specify)
64-17-5	10-20	ETHANOL	NA
74-88-6	20-30	PROPANE	NA
106-97-8	20-30	BUTANE	NA
26286-71-8	10-20	DIPROPYLENE GLYCOL	NA
111-90-0	5-10	DIETHYLENE GLYCOL MONOETHYL ETHER	NA
107-41-5	10-20	HEXYLENE GLYCOL	NA
67-63-0	10-20	ISOPROPYL ALCOHOL	NA
1	2-5	FRAGRANCE (Proprietary Mixture)	NE

- This product is a mixture for which no health hazard data exists. The hazard communications standard requires that such mixtures be assumed to present the same health hazard as do the components that constitute at least 1% of the mixture (.1% for carcinogens) although OSHA has noted that the hazards of individual components may be altered by including them in a mixture. This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right to Know Act and 40 CFR 372: NONE.
- Components of this product that are listed as Hazardous Materials and/or present in quantities as defined in OSHA 29 CFR 1910.1200: Isopropyl Alcohol.
- NE: Not Established.

SECTION III - PHYSICAL DATA

BOILING POINT: 132°F 55.56°C	SPECIFIC GRAVITY (H ₂ O=1): 0.824		
VAPOR PRESSURE: 74 MMHG	PERCENT VOLATILE BY VOLUME (%): NA	PERCENT SOLID BY WEIGHT (%): 0	
VAPOR DENSITY (AIR = 1): >1	EVAPORATION RATE (n-butyl acetate=1): >1		
SOLUBILITY IN WATER: Negligible	pH: NA		
APPEARANCE AND ODOR: Clear liquid, pleasantly scented.	IS MATERIAL: LIQUID SOLID GAS PASTE GEL		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 70°F 21.11°C	METHOD USED: TCC	FLAMMABLE LIMITS:	LEL 1.8	UEL 8.6
EXTINGUISHING MEDIA: Water, carbon dioxide, dry chemical or foam: Class A, BC or ABC Fire Extinguishers.				
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus and protective clothing should be worn in fighting fires.				
UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.				

SECTION V-HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: Eyes: Slight to moderate irritation. Skin: May cause minimal irritation. Inhalation: Not a significant route of exposure. Ingestion: Not a significant route of exposure and no significant adverse effects expected.	THRESHOLD LIMIT VALUE: Not determined.
---	---

OTHER LIMIT: NA

EMERGENCY AND FIRST AID PROCEDURES: **Inhalation:** Remove to fresh air. **Eye Contact:** Flush eyes with water; get medical attention if irritation persists. **Ingestion:** Administer lukewarm water (pint); DO NOT induce vomiting, call a physician.
Medical Conditions Aggravated by Exposure: None expected.

SECTION VI-REACTIVITY DATA

STABILITY:	UNSTABLE		CONDITIONS TO AVOID: NA
	STABLE	XXX	
INCOMPATIBILITY (materials to avoid): Strong oxidizing agents.			
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon containing materials when burned will produce carbon dioxide and carbon monoxide.			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID: NA
	WILL NOT OCCUR	XXX	

SECTION VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: No special clean-up procedures necessary. Remove all sources of flame, sparks, and heat. Provide adequate ventilation.	
WASTE DISPOSAL METHOD: Dispose in accordance with local, state and federal regulations.	
CERCLA (Superfund) REPORTABLE QUANTITY (In lbs): ND.	
RCRA HAZARDOUS WASTE NO. (40 CFR 261.33): D 001.	
VOLATILE ORGANIC COMPOUND (VOC) (as packaged, minus water): 70%.	
<input type="checkbox"/> Theoretical 7.42 lb/gal Intermediate w/o propellant	<input type="checkbox"/> Analytical: 7.42 lb/gal Intermediate w/o propellant.

SECTION VIII-SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (specify type): Not needed under normal circumstances.		
VENTILATION	LOCAL EXHAUST (Specify Rate): General room ventilation is normally sufficient.	SPECIAL: None.
	MECHANICAL (General) (Specify Rate): See above.	OTHER: None.
PROTECTIVE GLOVES (specify type): Not required.		EYE PROTECTION: Recommend safety glasses with side shields.
OTHER PROTECTIVE EQUIPMENT: None required.		

SECTION IX-SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid exposure to excessive heat and prevent from freezing.
OTHER PRECAUTIONS: None required.

This material safety data sheet is intended to meet the specific requirements of 29 CFR 1910.1200 and should be used accordingly. While the information has been obtained from sources believed to be accurate and reliable, no warranty, expressed or implied, can be made with regard to its completeness, correctness or accuracy. Any users or handlers of this product who are not under the direct control of Rubbermaid Commercial Products, Inc. are responsible for evaluating this information in light of their particular situation and are responsible for all losses, damages or expenses that result while this material is under their control. It is also the responsibility of the users and handlers to observe any and all laws and regulations (federal, state and local) concerning the transportation, use, handling, storage and disposal of this product.