MATERIAL SAFETY DATA SHEET

Product Name: GLASS BRITE

Product No. 063.00

SAVIN PRODUCTS COMPANY, INC.

| 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION | | | | |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|------------------------------------------------------------------|--------------------------------------------|-------------------|
| Product Name: GLASS BRITE | | | | |
| Emergency phone: Chemtrec 800-424-9300 | | Product Information: 781-961-2744 | | |
| Company: SAVIN PROI 214 HIGH ST RANDOLPH, | | 2. | | |
| Date Prepared: 1-14-04 | Super | rsedes: 10-02-03 | Prepared By: KJS | |
| 2. COMPOSITION / INFORMATION ON INGREDIENTS | | | | |
| Component | CAS No. | Exposure Limits | Ty | pical % by weight |
| 1. Isopropyl Alcohol | 67-63-0 | OSHA PEL: TWA 400 j TLV: 400 ppm (as TWA | | 5 – 10 |
| 2. Nonylphenol Ethoxylate | 9016-45-9 | N/A | | 1 -5 |
| 3. 2-Butoxyethanol | 111-76-2 | OSHA PEL†: TWA 50 j TLV: (as TWA) 20 ppm | ppm (240 mg/m3) [skin] ;; (ACGIH 2003). | 3-7 |
| † End of service life indicator (ESLI |) required | | | |
| 3. HAZARDS IDENTIFICATION | | | | |
| | | | | |
| EMERGENCY OVERVIEW CAUTION: Combustible. Causes eye irritation. May cause skin irritation with prolonged contact. Inhalation of mist may cause irritation to | | | | |
| | | e skin irritation with prolonge ed. Wash thoroughly after han | | |
| EFFECTS of OVEREXPOSURE: | | | | |
| | | | | |
| CARCINOGENICITY: NTP: No | IARC | 2: No O | SHA: No | |
| EYES: May cause severe eye irritation. SKIN: Repeated or prolonged contact may cause skin irritation. INHALATION: Mist may cause irritation to mucous membranes and respiratory tract. INGESTION: May result in gastric disturbances. | | | | |
| CHRONIC EFFECTS and MEDICA Safe handling of this material on a lo may aggravate existing eye, skin and | ong-term basis should emp | | | |

4. FIRST AID MEASURES

EYES: Flush with copious amounts of water for at least 15 minutes, lifting upper and lower lids occasionally. Get immediate medical attention. SKIN: Immediately flush with water. Remove contaminated clothing. Launder contaminated clothing before reuse. INHALATION: Remove to fresh air. If breathing is difficult, oxygen may be given, preferably with a physician's advice. Get medical attention. INGESTION: If swallowed, give several glasses of water. Do not induce vomiting. If vomiting does occur, give fluids again and keep head below hips to help prevent aspiration. Do not give anything by mouth to an unconscious person. Get immediate medical attention.

MATERIAL SAFETY DATA SHEET

Product Name: GLASS BRITE

Product No. 063.00

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES: Flash Point: 105° F Test: SETA CC, ASTM D-3278 Explosive Limits: LEL: N/A UEL: N/A NFPA/OSHA CLASS II EXTINGUISHING MEDIA: Use water spray for or foam, dry chemical, CO2 UNUSUAL FIRE and EXPLOSION HAZARDS: Large spills in a confined area could result in vapor concentrations which may produce a more serious fire hazard. FIREFIGHTING INSTRUCTIONS: Eirefighters should wear NIOSH approved positive pressure self-contained breathing apparatus and full

FIREFIGHTING INSTRUCTIONS: Firefighters should wear NIOSH approved, positive pressure, self-contained breathing apparatus and full protective clothing when appropriate.

6. ACCIDENTAL RELEASE MEASURES

WARNING: Combustible Material! Eliminate all ignition sources. Ventilate area! SMALL SPILLS: Soak up small spills with inert solids. Use suitable disposal container that is grounded and bonded. LARGE SPILLS: Evacuate Area! Wear appropriate respirator & protective clothing. Remove leaking containers to open air. Dilute spill with water to reduce combustion hazard. Absorb with sand, dirt or clay absorbents and deposit in suitable disposal containers and remove outside.

7. HANDLING AND STORAGE

Store in a clean, cool, ventilated area away from sources of ignition. Refer to NFPA 30 & OSHA 29CFR 1910.106 "Storage & Handling Combustible Liquids". Clean up spills at once. Electrically grounded handling equipment recommended. Keep container tightly closed when not in use. Protect containers from damage. Always wear appropriate protective clothing. Wash thoroughly after handling. FOR COMMERCIAL USE ONLY!

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION: Avoid splashing. Wear chemical-resistant safety goggles if necessary. Contact lenses must not be worn. PROTECTIVE GLOVES: Protective gloves for prolonged exposure.

RESPIRATORY PROTECTION: For prolonged exposure use NIOSH/MSHA approved respiratory protection equipment.

VENTILATION: Use adequate ventilation that would be equivalent to outdoor environment.

OTHER PROTECTIVE EQUIPMENT: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, pink, thin, foamy liquid. BOILING POINT: 180 – 300°F @ 1ATM VAPOR PRESSURE (mm): ca 20 mm Hg @ 70°F VAPOR DENSITY (air=1): ca 1.5 X Air EVAPORATION RATE: ca water SOLUBILITY IN WATER: Complete. DENSITY: 8.0 lb./gal. @ 20C pH(as is): 7.0 ODOR: Mild Alcohol odor. ODOR THRESHOLD (ppm): Not determined.

10. STABILITY AND REACTIVITY

CHEMICAL STABILITY (CONDITIONS TO AVOID): Stable. INCOMPATIBILITY: Strong acids, strong oxidizers and excessive heat. HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, Carbon Dioxide and other toxic gases when burning. HAZARDOUS POLYMERIZATION: None

11. TOXICOLOGICAL INFORMATION

No LD50 or LC50 found for oral, dermal or inhalation routes of administration.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL/CHEMICAL FATE INFORMATION: Not available.

MATERIAL SAFETY DATA SHEET

Product Name: GLASS BRITE

Product No. 063.00

13. DISPOSAL CONSIDERATIONS

RCRA: This product, if disposed as shipped, is considered a hazardous waste (IGNITABILITY) as specified in 40 CFR 261. Dispose in accordance with all applicable federal, state and local regulations.

14. TRANSPORT INFORMATION

SHIPPING NAME:Flammable Liquid, n.o.s. (Isopropyl Alcohol, 2- Butoxyethanol)HAZARD CLASS:Flammable LiquidID#UN1993PACKING GROUP:IIILABEL:FLAMMABLE LIQUID

15. REGULATORY INFORMATION

This material does not contain nor was it manufactured using ozone-depleting chemicals.

U.S. FEDERAL REGULATIONS:

TSCA STATUS: All ingredients on Toxic Substance Control Act Inventory.

CERCLA REPORTABLE QUANTITY: N/A

SARA TITLE III:

Section 302 Extremely Hazardous Substances: Section 311/312 Hazardous Categories: Section 313 Toxic Chemicals:

None. Fire Hazard/Immediate (Acute) Glycol Ether Category N230; 2-Butoxyethanol (CAS # 111-76-2)

16. OTHER INFORMATION

All label precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse this container unless it is professionally cleaned and reconditioned.

REFERENCES:

- U.S. Dept. of Health and Human Services, NIOSH: <u>Registry of Toxic Effects of Chemical Substances</u>, 1985-86 Edition.
- Sax, N. Irving and Lewis, R.J.: Dangerous Properties of Industrial Materials, 7th Edition, Van Nostrand Reinhold Co., 1989.
- Lewis, R.J.: <u>Hawley's Condensed Chemical Dictionary</u>,12th Edition, Van Nostrand Reinhold Co., 1993.
- U.S. Dept. of Transportation, U.S. Coast Guard: CHRIS Hazardous Chemical Data, 1982.
- U.S. Dept. of Labor, OSHA: Air Contaminants Permissible Exposure Limits, 1989.
- National Fire Protection Association (NFPA): <u>Fire Protection Guide on Hazardous Materials</u> (NFPA 325M/49/491M/704), 9th Edition, 1986.
- National Fire Protection Association (NFPA): <u>Hazardous Materials Response Handbook</u>, Henry, M.F., Editor, 1989.
- Merck & Co., Inc.: <u>The Merck Index</u>, 11th Edition, 1989.

Information herein is given in good faith as authoritative and valid; no warranty, express or implied can be made.