

Address:

MATERIAL SAFETY DATA SHEET



I. PRODUCT IDENTIFICATION

Manufacturer: WD-40 Company

1061 Cudahy Place (92110)

P.O. Box 80607

San Diego, California, USA

92138-0607

Telephone:

Emergency only: 1-888-324-7596 (PROZAR)

Information: (619) 275-1400

Chemical Name: Petroleum Hydrocarbon Mixture

Trade Name: 3-IN-ONE Professional Lubricant with PTFE

II. HAZARDOUS INGREDIENTS

Chemical Name	CAS Number	%	Exposure Limit ACGIH/OSHA
LVP Hydrocarbon Fluid	64742-47-8	30-40	1200 mg/m ³ (TWA)
Aliphatic Petroleum Distillates	8052-41-3	20-25	100 ppm (PEL)
Hydrocarbon Propellant	74-98-6	12-18	1000 ppm (PEL)
Petroleum Base Oil	64742-65-0	<15	5mg/m ³ (TWA) mist
PTFE/Oil	8002-059	1-4	5mg/m ³ (TWA) mist

III. PHYSICAL DATA

Boiling Point NA Evaporation Rate (Butyl Acetate=1): Less than 1

Vapor Density (air = 1): Greater than 1 Vapor Pressure: 60 +/- 5 PSI @ 70°F

Solubility in Water: insoluble Appearance: light amber Specific Gravity (H₂O) 0.816 @ 70° F Odor: pleasant odor

Percent Volatile (volume): 90.0%

IV. FIRE AND EXPLOSION

Flash Point: -20°F (Tag Closed CUP)

Flammable Limits: (Lel) 1.8% (Uel) 9.5% (Propellant Portion)

Extinguishing Media: CO₂, dry chemical, foam

Special Fire Fighting Procedures: EXTREMELY FLAMMABLE, UFC level 3 Aerosol

Unusual Fire and Explosion Hazards: Contents under pressure. Keep away from ignition source and open fire.

V. HEALTH HAZARD / ROUTE(S) OF ENTRY

Threshold Limit Value: Aliphatic Petroleum Distillates lowest TLV (ACGIH 100 ppm)

Symptoms of Overexposure:

Inhalation (Breathing):May cause anesthesia, headache, dizziness, nausea and upper respiratory irritation.

Skin contact: May cause drying of skin and/or irritation. **Eye contact:** May cause irritation, tearing and redness.

Ingestion (Swallowed): May cause irritation, nausea, vomiting and diarrhea.

First Aid Emergency Procedures:

Ingestion (Swallowed): Do not induce vomiting, seek medical attention.

Eye Contact: Immediately flush eyes with large amounts of water for 15 minutes.

Skin Contact: Wash with soap and water.

Inhalation (Breathing): Remove to fresh air. Give artificial respiration if necessary. If breathing is difficult, give

oxygen. Pre-existing medical conditions such as eye, skin and respiratory disorders

may be aggravated by exposure.

DANGER!

Aspiration Hazard: If swallowed, can enter lungs and may cause chemical pneumonitis. Do not induce

vomiting. Call physician immediately.

Suspected Cancer Agent The components in this mixture have been found to be noncarcinogenic by NTP, IARC

and OSHA.

Yes No X

VI. REACTIVITY DATA

Stability: Stable X Unstable:

Conditions to avoid: Heat and open flame Incompatibility: Strong oxidizing agents

Hazardous decomposition products: Carbon monoxide and/or carbon dioxide

Hazardous polymerization: May occur___ Will not occur__X_

VII. SPILL OR LEAK PROCEDURES

Spill Response Procedures

Spill unlikely from aerosol cans. Leaking cans should be placed in plastic bag or open pail until pressure has dissipated. **Waste Disposal Method**

Empty aerosol cans should not be punctured or incinerated; bury in land fill. Liquid should be incinerated or buried in land fill. Dispose of in accordance with local, state and federal regulations.

VIII. SPECIAL HANDLING INFORMATION

Ventilation: Sufficient to keep solvent vapor less than TLV.
Respiratory Protection: Advised when concentrations exceed TLV.
Protective Gloves: Advised to prevent possible skin irritation.

Eye Protection: Approved eye protections to safeguard against potential eye contact, irritation or injury.

Other Protective Equipment: None required.

IX. SPECIAL PRECAUTIONS

Keep from sources of ignition. Avoid excessive inhalation of spray particles, do not take internally. Do not puncture, incinerate or store container above 120°F. Exposure to heat may cause bursting. Keep can away from electrical current or battery terminals. Electrical arcing can cause burn-through (puncture) which may result in flash fire, causing serious injury. Keep from children.

X. REGULATORY INFORMATION

Αll	l ingredients	for this pro	duct are lis	sted on the	TSCA inventory	١.

SARA Title III chemicals:
California Prop 65 chemicals:
CERCLA reportable quantity:
RCRA hazardous waste no:
None
D001

SIGNATURE: Peter Fougner TITLE: ______ Director of Global Quality Assurance REVISION DATE: ______ December, 2004 SUPERSEDES: _____ February, 2004

NA: Not applicable NDA: No data available (= Less than) = More than

We believe the statements, technical information and recommendations contained herein are reliable. However, the data is provided without warranty, expressed or implied. It is the user's responsibility both to determine safe conditions for use of this product and assume loss, damage or expense, direct or consequential, arising from its use. Before using product, read label.